

Amazon

Exam Questions AWS-Certified-Security-Specialty

Amazon AWS Certified Security - Specialty



NEW QUESTION 1

You are hosting a web site via website hosting on an S3 bucket - <http://demo.s3-website-us-east-1.amazonaws.com>. You have some web pages that use Javascript that access resources in another bucket which has web site hosting also enabled. But when users access the web pages, they are getting a blocked Javascript error. How can you rectify this? Please select:

- A. Enable CORS for the bucket
- B. Enable versioning for the bucket
- C. Enable MFA for the bucket
- D. Enable CRR for the bucket

Answer: A

Explanation:

Your answer is incorrect Answer-A

Such a scenario is also given in the AWS Documentation Cross-Origin Resource Sharing:

Use-case Scenarios

The following are example scenarios for using CORS:

- Scenario 1: Suppose that you are hosting a website in an Amazon S3 bucket named website as described in Hosting a Static Website on Amazon S3. Your users load the website endpoint <http://website.s3-website-us-east-1.amazonaws.com>. Now you want to use JavaScript on the webpages that are stored in this bucket to be able to make authenticated GET and PUT requests against the same bucket by using the Amazon S3 API endpoint for the bucket website.s3.amazonaws.com. A browser would normally block JavaScript from allowing those requests, but with CORS you can configure your bucket to explicitly enable cross-origin requests from website.s3-website-us-east-1.amazonaws.com.
- Scenario 2: Suppose that you want to host a web font from your S3 bucket. Again, browsers require a CORS check (also called a preflight check) for loading web fonts. You would configure the bucket that is hosting the web font to allow any origin to make these requests.

Option B is invalid because versioning is only to create multiple versions of an object and can help in accidental deletion of objects

Option C is invalid because this is used as an extra measure of caution for deletion of objects Option D is invalid because this is used for Cross region replication of objects

For more information on Cross Origin Resource sharing, please visit the following URL

- <https://docs.aws.amazon.com/AmazonS3/latest/dev/cors.html>

The correct answer is: Enable CORS for the bucket

Submit your Feedback/Queries to our Experts

NEW QUESTION 2

Your company has an EC2 Instance that is hosted in an AWS VPC. There is a requirement to ensure that logs files from the EC2 Instance are stored accordingly. The access should also be limited for the destination of the log files. How can this be accomplished? Choose 2 answers from the options given below. Each answer forms part of the solution Please select:

- A. Stream the log files to a separate Cloudtrail trail
- B. Stream the log files to a separate Cloudwatch Log group
- C. Create an IAM policy that gives the desired level of access to the Cloudtrail trail
- D. Create an IAM policy that gives the desired level of access to the Cloudwatch Log group

Answer: BD

Explanation:

You can create a Log group and send all logs from the EC2 Instance to that group. You can then limit the access to the Log groups via an IAM policy.

Option A is invalid because Cloudtrail is used to record API activity and not for storing log files Option C is invalid because Cloudtrail is the wrong service to be used for this requirement

For more information on Log Groups and Log Streams, please visit the following URL:

- * <https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/Working>

For more information on Access to Cloudwatch logs, please visit the following URL:

- * <https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/auth-and-access-control-cwl.html> The correct answers are: Stream the log files to a separate Cloudwatch Log group. Create an IAM policy that gives the desired level of access to the Cloudwatch Log group

Submit your Feedback/Queries to our Experts

NEW QUESTION 3

You have a web site that is sitting behind AWS Cloudfront. You need to protect the web site against threats such as SQL injection and Cross site scripting attacks. Which of the following service can help in such a scenario Please select:

- A. AWS Trusted Advisor
- B. AWS WAF
- C. AWS Inspector
- D. AWS Config

Answer: B

Explanation:

The AWS Documentation mentions the following

AWS WAF is a web application firewall that helps detect and block malicious web requests targeted at your web applications. AWS WAF allows you to create rules that can help protect against common

web exploits like SQL injection and cross-site scripting. With AWS WAF you first identify the resource (either an Amazon CloudFront distribution or an Application Load Balancer) that you need to protect. Option A is invalid because this will only give advise on how you can better the security in your AWS account but not protect against threats mentioned in the question.

Option C is invalid because this can be used to scan EC2 Instances for vulnerabilities but not protect against threats mentioned in the question.

Option D is invalid because this can be used to check config changes but not protect against threats mentioned in the quest

For more information on AWS WAF, please visit the following URL: <https://aws.amazon.com/waf/details>;

The correct answer is: AWS WAF
Submit your Feedback/Queries to our Experts

NEW QUESTION 4

You have an S3 bucket hosted in AWS. This is used to host promotional videos uploaded by yourself. You need to provide access to users for a limited duration of time. How can this be achieved?

Please select:

- A. Use versioning and enable a timestamp for each version
- B. Use Pre-signed URL's
- C. Use IAM Roles with a timestamp to limit the access
- D. Use IAM policies with a timestamp to limit the access

Answer: B

Explanation:

The AWS Documentation mentions the following

All objects by default are private. Only the object owner has permission to access these objects. However, the object owner can optionally share objects with others by creating a pre-signed URL using their own security credentials, to grant time-limited permission to download the objects. Option A is invalid because this can be used to prevent accidental deletion of objects

Option C is invalid because timestamps are not possible for Roles

Option D is invalid because policies is not the right way to limit access based on time For more information on pre-signed URL's, please visit the URL:

<https://docs.aws.amazon.com/AmazonS3/latest/dev/ShareObjectPreSignedURL.html>

The correct answer is: Use Pre-signed URL's Submit your Feedback/Queries to our Experts

NEW QUESTION 5

Your company has mandated that all calls to the AWS KMS service be recorded. How can this be achieved?

Please select:

- A. Enable logging on the KMS service
- B. Enable a trail in Cloudtrail
- C. Enable Cloudwatch logs
- D. Use Cloudwatch metrics

Answer: B

Explanation:

The AWS Documentation states the following

AWS KMS is integrated with CloudTrail, a service that captures API calls made by or on behalf of AWS KMS in your AWS account and delivers the log files to an Amazon S3 bucket that you specify. CloudTrail captures API calls from the AWS KMS console or from the AWS KMS API. Using the information collected by CloudTrail, you can determine what request was made, the source IP

address from which the request was made, who made the request when it was made, and so on. Option A is invalid because logging is not possible in the KMS service

Option C and D are invalid because Cloudwatch cannot be used to monitor API calls For more information on logging using Cloudtrail please visit the below URL

<https://docs.aws.amazon.com/kms/latest/developerguide/loeeing-usine-cloudtrail.html> The correct answer is: Enable a trail in Cloudtrail

Submit your Feedback/Queries to our Experts

NEW QUESTION 6

Your company has defined a number of EC2 Instances over a period of 6 months. They want to know if any of the security groups allow unrestricted access to a resource. What is the best option to accomplish this requirement?

Please select:

- A. Use AWS Inspector to inspect all the security Groups
- B. Use the AWS Trusted Advisor to see which security groups have compromised access.
- C. Use AWS Config to see which security groups have compromised access.
- D. Use the AWS CLI to query the security groups and then filter for the rules which have unrestricted access

Answer: B

Explanation:

The AWS Trusted Advisor can check security groups for rules that allow unrestricted access to a resource. Unrestricted access increases opportunities for malicious activity (hacking, denial-of-service attacks, loss of data).

If you go to AWS Trusted Advisor, you can see the details

Option A is invalid because AWS Inspector is used to detect security vulnerabilities in instances and not for security groups.

Option C is invalid because this can be used to detect changes in security groups but not show you security groups that have compromised access.

Option D is partially valid but would just be a maintenance overhead

For more information on the AWS Trusted Advisor, please visit the below URL: <https://aws.amazon.com/premiumsupport/trustedadvisor/best-practices>;

The correct answer is: Use the AWS Trusted Advisor to see which security groups have compromised access. Submit your Feedback/Queries to our Experts

NEW QUESTION 7

You have just received an email from AWS Support stating that your AWS account might have been compromised. Which of the following steps would you look to carry out immediately. Choose 3 answers from the options below.

Please select:

- A. Change the root account password.
- B. Rotate all IAM access keys
- C. Keep all resources running to avoid disruption
- D. Change the password for all IAM user

Answer: ABD

Explanation:

One of the articles from AWS mentions what should be done in such a scenario

If you suspect that your account has been compromised, or if you have received a notification from AWS that the account has been compromised, perform the following tasks:

Change your AWS root account password and the passwords of any IAM users. Delete or rotate all root and AWS Identity and Access Management (IAM) access keys.

Delete any resources on your account you didn't create, especially running EC2 instances, EC2 spot bids, or IAM users.

Respond to any notifications you received from AWS Support through the AWS Support Center. Option C is invalid because there could be compromised instances or resources running on your environment. They should be shutdown or stopped immediately.

For more information on the article, please visit the below URL: <https://aws.amazon.com/premiumsupport/knowledge-center/potential-account-compromise>

The correct answers are: Change the root account password. Rotate all IAM access keys. Change the password for all IAM users. Submit your Feedback/Queries to our Experts

NEW QUESTION 8

You have enabled Cloudtrail logs for your company's AWS account. In addition, the IT Security department has mentioned that the logs need to be encrypted. How can this be achieved?

Please select:

- A. Enable SSL certificates for the Cloudtrail logs
- B. There is no need to do anything since the logs will already be encrypted
- C. Enable Server side encryption for the trail
- D. Enable Server side encryption for the destination S3 bucket

Answer: B

Explanation:

The AWS Documentation mentions the following.

By default CloudTrail event log files are encrypted using Amazon S3 server-side encryption (SSE). You can also choose to encryption your log files with an AWS Key Management Service (AWS KMS) key. You can store your log files in your bucket for as long as you want. You can also define Amazon S3 lifecycle rules to archive or delete log files automatically. If you want notifications about log file delivery and validation, you can set up Amazon SNS notifications.

Option A,C and D are not valid since logs will already be encrypted

For more information on how Cloudtrail works, please visit the following URL: <https://docs.aws.amazon.com/awsccloudtrail/latest/userguide/how-cloudtrail-works.html>

The correct answer is: There is no need to do anything since the logs will already be encrypted Submit your Feedback/Queries to our Experts

NEW QUESTION 9

A company has a legacy application that outputs all logs to a local text file. Logs from all applications running on AWS must be continually monitored for security related messages.

What can be done to allow the company to deploy the legacy application on Amazon EC2 and still meet the monitoring requirement? Please select:

- A. Create a Lambda function that mounts the EBS volume with the logs and scans the logs for security incident
- B. Trigger the function every 5 minutes with a scheduled Cloudwatch event.
- C. Send the local text log files to CloudWatch Logs and configure a CloudWatch metric filter
- D. Trigger cloudwatch alarms based on the metrics.
- E. Install the Amazon inspector agent on any EC2 instance running the legacy application
- F. Generate CloudWatch alerts based on any Amazon inspector findings.
- G. Export the local text log files to CloudTrail
- H. Create a Lambda function that queries the CloudTrail logs for security incidents using Athena.

Answer: B

Explanation:

One can send the log files to Cloudwatch Logs. Log files can also be sent from On-premise servers. You can then specify metrics to search the logs for any specific values. And then create alarms based on these metrics.

Option A is invalid because this will be just a long over drawn process to achieve this requirement Option C is invalid because AWS Inspector cannot be used to monitor for security related messages. Option D is invalid because files cannot be exported to AWS Cloudtrail

For more information on Cloudwatch logs agent please visit the below URL:

<https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/QuickStartEC2Instance.html>

The correct answer is: Send the local text log files to Cloudwatch Logs and configure a Cloudwatch metric filter. Trigger cloudwatch alarms based on the metrics. Submit your Feedback/Queries to our Experts

NEW QUESTION 10

A company is deploying a new web application on AWS. Based on their other web applications, they anticipate being the target of frequent DDoS attacks. Which steps can the company use to protect their application? Select 2 answers from the options given below.

Please select:

- A. Associate the EC2 instances with a security group that blocks traffic from blacklisted IP addresses.
- B. Use an ELB Application Load Balancer and Auto Scaling group to scale to absorb application layer traffic.
- C. Use Amazon Inspector on the EC2 instances to examine incoming traffic and discard malicious traffic.
- D. Use CloudFront and AWS WAF to prevent malicious traffic from reaching the application
- E. Enable GuardDuty to block malicious traffic from reaching the application

Answer: BD

Explanation:

The below diagram from AWS shows the best case scenario for avoiding DDoS attacks using services such as AWS CloudFront WAF, ELB and Autoscaling

Option A is invalid because by default security groups don't allow access Option C is invalid because AWS Inspector cannot be used to examine traffic Option E is invalid because this can be used for attacks on EC2 Instances but not against DDos attacks on the entire application For more information on DDos mitigation from AWS, please visit the below URL:

<https://aws.amazon.com/answers/networking/aws-ddos-attack-mitigation/>

The correct answers are: Use an ELB Application Load Balancer and Auto Scaling group to scale to absorb application layer traffic., Use CloudFront and AWS WAF to prevent malicious traffic from reaching the application
Submit your Feedback/Queries to our Experts

NEW QUESTION 10

You have a set of Keys defined using the AWS KMS service. You want to stop using a couple of keys, but are not sure of which services are currently using the keys. Which of the following would be a safe option to stop using the keys from further usage. Please select:

- A. Delete the keys since anyway there is a 7 day waiting period before deletion
- B. Disable the keys
- C. Set an alias for the key
- D. Change the key material for the key

Answer: B

Explanation:

Option A is invalid because once you schedule the deletion and waiting period ends, you cannot come back from the deletion process.

Option C and D are invalid because these will not check to see if the keys are being used or not The AWS Documentation mentions the following

Deleting a customer master key (CMK) in AWS Key Management Service (AWS KMS) is destructive and potentially dangerous. It deletes the key material and all metadata associated with the CMK, and is irreversible. After a CMK is deleted you can no longer decrypt the data that was encrypted under that CMK, which means that data becomes unrecoverable. You should delete a CMK only when you are sure that you don't need to use it anymore. If you are not sure, consider disabling the CMK

instead of deleting it. You can re-enable a disabled CMK if you need to use it again later, but you cannot recover a deleted CMK.

For more information on deleting keys from KMS, please visit the below URL: <https://docs.aws.amazon.com/kms/latest/developerguide/deleting-keys.html>

The correct answer is: Disable the keys Submit your Feedback/Queries to our Experts

NEW QUESTION 14

You are building a large-scale confidential documentation web server on AWS and all of the documentation for it will be stored on S3. One of the requirements is that it cannot be publicly accessible from S3 directly, and you will need to use Cloud Front to accomplish this. Which of the methods listed below would satisfy the requirements as outlined? Choose an answer from the options below
Please select:

- A. Create an Identity and Access Management (IAM) user for CloudFront and grant access to the objects in your S3 bucket to that IAM User.
- B. Create an Origin Access Identity (OAI) for CloudFront and grant access to the objects in your S3 bucket to that OAI.
- C. Create individual policies for each bucket the documents are stored in and in that policy grant access to only CloudFront.
- D. Create an S3 bucket policy that lists the CloudFront distribution ID as the Principal and the target bucket as the Amazon Resource Name (ARN).

Answer: B

Explanation:

If you want to use CloudFront signed URLs or signed cookies to provide access to objects in your Amazon S3 bucket you probably also want to prevent users from

accessing your Amazon S3 objects using Amazon S3 URLs. If users access your objects directly in Amazon S3, they bypass the controls provided by CloudFront signed URLs or signed cookies, for example, control over the date and time that a user can no longer access your content and control over which IP addresses can be used to access content. In addition, if user's access objects both through CloudFront and directly by using Amazon S3 URLs, CloudFront access logs are less useful because they're incomplete.

Option A is invalid because you need to create a Origin Access Identity for Cloudfront and not an IAM user

Option C and D are invalid because using policies will not help fulfil the requirement For more information on Origin Access Identity please see the below Link:

<http://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/private-contentrestrictions-access-to-s3.html>

The correct answer is: Create an Origin Access Identity (OAI) for CloudFront and grant access to the objects in your S3 bucket to that OAI.

(

Submit your Feedback/Queries to our Experts

NEW QUESTION 17

Your company makes use of S3 buckets for storing data

- A. There is a company policy that all services should have logging enabled
- B. How can you ensure that logging is always enabled for created S3 buckets in the AWS Account? Please select:
- C. Use AWS Inspector to inspect all S3 buckets and enable logging for those where it is not enabled
- D. Use AWS Config Rules to check whether logging is enabled for buckets
- E. Use AWS Cloudwatch metrics to check whether logging is enabled for buckets
- F. Use AWS Cloudwatch logs to check whether logging is enabled for buckets

Answer: B

Explanation:

This is given in the AWS Documentation as an example rule in AWS Config Example rules with triggers

Example rule with configuration change trigger

1. You add the AWS Config managed rule, S3_BUCKET_LOGGING_ENABLED, to your account to check whether your Amazon S3 buckets have logging enabled.
2. The trigger type for the rule is configuration changes. AWS Config runs the evaluations for the rule when an Amazon S3 bucket is created, changed, or deleted.
3. When a bucket is updated, the configuration change triggers the rule and AWS Config evaluates whether the bucket is compliant against the rule.

Option A is invalid because AWS Inspector cannot be used to scan all buckets

Option C and D are invalid because Cloudwatch cannot be used to check for logging enablement for buckets.

For more information on Config Rules please see the below Link: <https://docs.aws.amazon.com/config/latest/developerguide/evaluate-config-rules.html>

The correct answer is: Use AWS Config Rules to check whether logging is enabled for buckets Submit your Feedback/Queries to our Experts

NEW QUESTION 18

Your current setup in AWS consists of the following architecture. 2 public subnets, one subnet which has the web servers accessed by users across the internet and the other subnet for the database server. Which of the following changes to the architecture would add a better security boundary to the resources hosted in your setup

Please select:

- A. Consider moving the web server to a private subnet
- B. Consider moving the database server to a private subnet
- C. Consider moving both the web and database server to a private subnet
- D. Consider creating a private subnet and adding a NAT instance to that subnet

Answer: B

Explanation:

The ideal setup is to ensure that the web server is hosted in the public subnet so that it can be accessed by users on the internet. The database server can be hosted in the private subnet. The below diagram from the AWS Documentation shows how this can be setup

Option A and C are invalid because if you move the web server to a private subnet, then it cannot be accessed by users Option D is invalid because NAT instances should be present in the public subnet For more information on public and private subnets in AWS, please visit the following url https://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Scenario2.html

The correct answer is: Consider moving the database server to a private subnet Submit your Feedback/Queries to our Experts

NEW QUESTION 20

Your company has confidential documents stored in the simple storage service. Due to compliance requirements, you have to ensure that the data in the S3 bucket is available in a different geographical location. As an architect what is the change you would make to comply with this requirement.

Please select:

- A. Apply Multi-AZ for the underlying S3 bucket
- B. Copy the data to an EBS Volume in another Region
- C. Create a snapshot of the S3 bucket and copy it to another region
- D. Enable Cross region replication for the S3 bucket

Answer: D

Explanation:

This is mentioned clearly as a use case for S3 cross-region replication

You might configure cross-region replication on a bucket for various reasons, including the following:

- Compliance requirements - Although, by default Amazon S3 stores your data across multiple geographically distant Availability Zones, compliance requirements might dictate that you store data at even further distances. Cross-region replication allows you to replicate data between distant AWS Regions to satisfy these compliance requirements.

Option A is invalid because Multi-AZ cannot be used to S3 buckets

Option B is invalid because copying it to an EBS volume is not a recommended practice Option C is invalid because creating snapshots is not possible in S3

For more information on S3 cross-region replication, please visit the following URL: <https://docs.aws.amazon.com/AmazonS3/latest/dev/crr.html>

The correct answer is: Enable Cross region replication for the S3 bucket Submit your Feedback/Queries to our Experts

NEW QUESTION 23

A company hosts data in S3. There is a requirement to control access to the S3 buckets. Which are the 2 ways in which this can be achieved?
 Please select:

- A. Use Bucket policies
- B. Use the Secure Token service
- C. Use IAM user policies
- D. Use AWS Access Keys

Answer: AC

Explanation:

The AWS Documentation mentions the following

Amazon S3 offers access policy options broadly categorized as resource-based policies and user policies. Access policies you attach to your resources (buckets and objects) are referred to as resource-based policies. For example, bucket policies and access control lists (ACLs) are resourcebased policies. You can also attach access policies to users in your account. These are called user policies. You may choose to use resource-based policies, user policies, or some combination of these to manage permissions to your Amazon S3 resources. Option B and D are invalid because these cannot be used to control access to S3 buckets For more information on S3 access control, please refer to the below Link: <https://docs.aws.amazon.com/AmazonS3/latest/dev/s3-access-control.html>

The correct answers are: Use Bucket policies. Use IAM user policies Submit your Feedback/Queries to our Experts

NEW QUESTION 27

A company continually generates sensitive records that it stores in an S3 bucket. All objects in the bucket are encrypted using SSE-KMS using one of the company's CMKs. Company compliance policies require that no more than one month of data be encrypted using the same encryption key. What solution below will meet the company's requirements?

Please select:

- A. Trigger a Lambda function with a monthly CloudWatch event that creates a new CMK and updates the S3 bucket to use the new CMK.
- B. Configure the CMK to rotate the key material every month.
- C. Trigger a Lambda function with a monthly CloudWatch event that creates a new CMK, updates the S3 bucket to use thfl new CMK, and deletes the old CMK.
- D. Trigger a Lambda function with a monthly CloudWatch event that rotates the key material in the CMK.

Answer: A

Explanation:

You can use a Lambda function to create a new key and then update the S3 bucket to use the new key. Remember not to delete the old key, else you will not be able to decrypt the documents stored in the S3 bucket using the older key.

Option B is incorrect because AWS KMS cannot rotate keys on a monthly basis

Option C is incorrect because deleting the old key means that you cannot access the older objects Option D is incorrect because rotating key material is not possible.

For more information on AWS KMS keys, please refer to below URL: <https://docs.aws.amazon.com/kms/latest/developereuide/concepts.html>

The correct answer is: Trigger a Lambda function with a monthly CloudWatch event that creates a new CMK and updates the S3 bucket to use the new CMK.

Submit your Feedback/Queries to our Experts

NEW QUESTION 31

A web application runs in a VPC on EC2 instances behind an ELB Application Load Balancer. The application stores data in an RDS MySQL DB instance. A Linux bastion host is used to apply schema updates to the database - administrators connect to the host via SSH from a corporate workstation. The following security groups are applied to the infrastructure-

* sgLB - associated with the ELB

* sgWeb - associated with the EC2 instances.

* sgDB - associated with the database

* sgBastion - associated with the bastion host Which security group configuration will allow the application to be secure and functional?

Please select: A.

sgLB :allow port 80 and 443 traffic from 0.0.0.0/0 sgWeb :allow port 80 and 443 traffic from 0.0.0.0/0 sgDB :allow port 3306 traffic from sgWeb and sgBastion

sgBastion: allow port 22 traffic from the corporate IP address range

B.

sgLB :allow port 80 and 443 traffic from 0.0.0.0/0 sgWeb :allow port 80 and 443 traffic from sgLB sgDB :allow port 3306 traffic from sgWeb and sgLB

sgBastion: allow port 22 traffic from the VPC IP address range C.

sgLB :allow port 80 and 443 traffic from 0.0.0.0/0 sgWeb :allow port 80 and 443 traffic from sgLB

sgDB :allow port 3306 traffic from sgWeb and sgBastion sgBastion: allow port 22 traffic from the VPC IP address range D.

sgLB :allow port 80 and 443 traffic from 0.0.0.0/0 sgWeb :allow port 80 and 443 traffic from sgLB

sgDB :allow port 3306 traffic from sgWeb and sgBastion sgBastion: allow port 22 traffic from the corporate IP address range

A.

Answer: D

Explanation:

The Load Balancer should accept traffic on ow port 80 and 443 traffic from 0.0.0.0/0 The backend EC2 Instances should accept traffic from the Load Balancer

The database should allow traffic from the Web server

And the Bastion host should only allow traffic from a specific corporate IP address range Option A is incorrect because the Web group should only allow traffic from the Load balancer For more information on AWS Security Groups, please refer to below URL: <https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/usins-network-security.html>

The correct answer is: sgLB :allow port 80 and 443 traffic from 0.0.0.0/0 sgWeb :allow port 80 and 443 traffic from sgLB

sgDB :allow port 3306 traffic from sgWeb and sgBastion sgBastion: allow port 22 traffic from the corporate IP address range Submit your Feedback/Queries to our Experts

NEW QUESTION 32

You need to have a cloud security device which would allow to generate encryption keys based on FIPS 140-2 Level 3. Which of the following can be used for this

purpose.
Please select:

- A. AWS KMS
- B. AWS Customer Keys
- C. AWS managed keys
- D. AWS Cloud HSM

Answer: AD

Explanation:

AWS Key Management Service (KMS) now uses FIPS 140-2 validated hardware security modules (HSM) and supports FIPS 140-2 validated endpoints, which provide independent assurances about the confidentiality and integrity of your keys.

All master keys in AWS KMS regardless of their creation date or origin are automatically protected using FIPS 140-2 validated HSMs. defines four levels of security, simply named "Level 1" to "Level 4". It does not specify in detail what level of security is required by any particular application.

- FIPS 140-2 Level 1 the lowest, imposes very limited requirements; loosely, all components must be "production-grade" and various egregious kinds of insecurity must be absent
- FIPS 140-2 Level 2 adds requirements for physical tamper-evidence and role-based authentication.
- FIPS 140-2 Level 3 adds requirements for physical tamper-resistance (making it difficult for attackers to gain access to sensitive information contained in the module) and identity-based authentication, and for a physical or logical separation between the interfaces by which "critical security parameters" enter and leave the module, and its other interfaces.
- FIPS 140-2 Level 4 makes the physical security requirements more stringent and requires robustness against environmental attacks.

AWS CloudHSM provides you with a FIPS 140-2 Level 3 validated single-tenant HSM cluster in your Amazon Virtual Private Cloud (VPC) to store and use your keys. You have exclusive control over how your keys are used via an authentication mechanism independent from AWS. You interact with keys in your AWS CloudHSM cluster similar to the way you interact with your applications running in Amazon EC2.

AWS KMS allows you to create and control the encryption keys used by your applications and supported AWS services in multiple regions around the world from a single console. The service uses a FIPS 140-2 validated HSM to protect the security of your keys. Centralized management of all your keys in AWS KMS lets you enforce who can use your keys under which conditions, when they get rotated, and who can manage them.

AWS KMS HSMs are validated at level 2 overall and at level 3 in the following areas:

- Cryptographic Module Specification
- Roles, Services, and Authentication
- Physical Security
- Design Assurance

So I think that we can have 2 answers for this question. Both A & D.

- <https://aws.amazon.com/blogs/security/aws-key-management-service-now-offers-fips-140-2-validated-cryptographic-modules-enabling-easier-adoption-of-the-service-for-regulated-workloads/>
- <https://aws.amazon.com/cloudhsm/faqs/>
- <https://aws.amazon.com/kms/faqs/>
- <https://en.wikipedia.org/wiki/RPS>

The AWS Documentation mentions the following

AWS CloudHSM is a cloud-based hardware security module (HSM) that enables you to easily generate and use your own encryption keys on the AWS Cloud.

With CloudHSM, you can manage your own encryption keys using FIPS 140-2 Level 3 validated HSMs. CloudHSM offers you the flexibility to integrate with your applications using industry-standard APIs, such as PKCS#11, Java

Cryptography Extensions (JCE), and Microsoft CryptoNG (CNG) libraries. CloudHSM is also standards-compliant and enables you to export all of your keys to most other commercially-available HSMs. It is a fully-managed service that automates time-consuming administrative tasks for you, such as hardware provisioning, software patching, high-availability, and backups. CloudHSM also enables you to scale quickly by adding and removing HSM capacity on-demand, with no up-front costs.

All other options are invalid since AWS Cloud HSM is the prime service that offers FIPS 140-2 Level 3 compliance

For more information on CloudHSM, please visit the following url <https://aws.amazon.com/cloudhsm/>;

The correct answers are: AWS KMS, AWS Cloud HSM Submit your Feedback/Queries to our Experts

NEW QUESTION 35

A company stores critical data in an S3 bucket. There is a requirement to ensure that an extra level of security is added to the S3 bucket. In addition, it should be ensured that objects are available in a secondary region if the primary one goes down. Which of the following can help fulfil these requirements? Choose 2 answers from the options given below

Please select:

- A. Enable bucket versioning and also enable CRR
- B. Enable bucket versioning and enable Master Pays
- C. For the Bucket policy add a condition for {"Null": {"aws:MultiFactorAuthAge": true}}
- D. Enable the Bucket ACL and add a condition for {"Null": {"aws:MultiFactorAuthAge": true}}

Answer: AC

Explanation:

The AWS Documentation mentions the following Adding a Bucket Policy to Require MFA

Amazon S3 supports MFA-protected API access, a feature that can enforce multi-factor authentication (MFA) for access to your Amazon S3 resources. Multi-factor authentication provides an extra level of security you can apply to your AWS environment. It is a security feature that requires users to prove physical possession of an MFA device by providing a valid MFA code. For more information, go to AWS Multi-Factor Authentication. You can require MFA authentication for any requests to access your Amazon S3 resources.

You can enforce the MFA authentication requirement using the aws:MultiFactorAuthAge key in a bucket policy. IAM users can access Amazon S3 resources by using temporary credentials issued by the AWS Security Token Service (STS). You provide the MFA code at the time of the STS request. When Amazon S3 receives a request with MFA authentication, the aws:MultiFactorAuthAge key provides a numeric value indicating how long ago (in seconds) the temporary credential was created. If the temporary credential provided in the request was not created using an MFA device, this key value is null (absent). In a bucket policy, you can add a condition to check this value, as shown in the following example bucket policy. The policy denies any Amazon S3 operation on the /taxdocuments folder in the examplebucket bucket if the request is not MFA authenticated. To learn more about MFA authentication, see Using Multi-Factor Authentication (MFA) in AWS in the IAM User Guide.

Option B is invalid because just enabling bucket versioning will not guarantee replication of objects Option D is invalid because the condition for the bucket policy needs to be set accordingly For more information on example bucket policies, please visit the following URL: •

<https://docs.aws.amazon.com/AmazonS3/latest/dev/example-bucket-policies.html>

Also versioning and Cross Region replication can ensure that objects will be available in the destination region in case the primary region fails.
For more information on CRR, please visit the following URL: <https://docs.aws.amazon.com/AmazonS3/latest/dev/crr.html>
The correct answers are: Enable bucket versioning and also enable CRR, For the Bucket policy add a condition for {"Null": { "aws:MultiFactorAuthAge": true}}
Submit your Feedback/Queries to our Experts

NEW QUESTION 38

You are trying to use the AWS Systems Manager run command on a set of Instances. The run command on a set of Instances. What can you do to diagnose the issue? Choose 2 answers from the options given
Please select:

- A. Ensure that the SSM agent is running on the target machine
- B. Check the /var/log/amazon/ssm/errors.log file
- C. Ensure the right AMI is used for the Instance
- D. Ensure the security groups allow outbound communication for the instance

Answer: AB

Explanation:

The AWS Documentation mentions the following
If you experience problems executing commands using Run Command, there might be a problem with the SSM Agent. Use the following information to help you troubleshoot the agent

View Agent Logs

The SSM Agent logs information in the following files. The information in these files can help you troubleshoot problems.

On Windows

%PROGRAMDATA%\Amazon\SSM\Log\amazon-ssm-agent.log

%PROGRAMDATA%\Amazon\SSM\Log\error.log

The default filename of the seelog is seelog-xml.template. If you modify a seelog, you must rename the file to seelog.xml.

On Linux

/var/log/amazon/ssm/amazon-ssm-agentlog /var/log/amazon/ssm/errors.log

Option C is invalid because the right AMI has nothing to do with the issues. The agent which is used to execute run commands can run on a variety of AMI'S

Option D is invalid because security groups does not come into the picture with the communication between the agent and the SSM service

For more information on troubleshooting AWS SSM, please visit the following URL: <https://docs.aws.amazon.com/systems-manageer/latest/userguide/troubleshootine-remotecommands.html>

The correct answers are: Ensure that the SSM agent is running on the target machine. Check the

/var/log/amazon/ssm/errors.log file

Submit your Feedback/Queries to our Experts

NEW QUESTION 42

Which technique can be used to integrate AWS IAM (Identity and Access Management) with an on Questions & Answers PDF P-63 premise LDAP (Lightweight Directory Access Protocol) directory service? Please select:

- A. Use an IAM policy that references the LDAP account identifiers and the AWS credentials.
- B. Use SAML (Security Assertion Markup Language) to enable single sign-on between AWS and LDAP.
- C. Use AWS Security Token Service from an identity broker to issue short-lived AWS credentials.
- D. Use IAM roles to automatically rotate the IAM credentials when LDAP credentials are update

Answer: B

Explanation:

On the AWS Blog site the following information is present to help on this context

The newly released whitepaper. Single Sign-On: Integrating AWS, OpenLDAP, and Shibboleth, will help you integrate your existing LDAP-based user directory with AWS. When you integrate your existing directory with AWS, your users can access AWS by using their existing credentials. This means that your users don't need to maintain yet another user name and password just to access AWS resources.

Option A.C and D are all invalid because in this sort of configuration, you have to use SAML to enable single sign on.

For more information on integrating AWS with LDAP for Single Sign-On, please visit the following URL:

<https://aws.amazon.com/blogs/security/new-whitepaper-single-sign-on-integrating-aws-openldap-and-shibboleth/>

The correct answer is: Use SAML (Security Assertion Markup Language) to enable single sign-on between AWS and LDAP. Submit your Feedback/Queries to our Experts

NEW QUESTION 43

Your application currently uses customer keys which are generated via AWS KMS in the US east region. You now want to use the same set of keys from the EU-Central region. How can this be accomplished?
Please select:

- A. Export the key from the US east region and import them into the EU-Central region
- B. Use key rotation and rotate the existing keys to the EU-Central region
- C. Use the backing key from the US east region and use it in the EU-Central region
- D. This is not possible since keys from KMS are region specific

Answer: D

Explanation:

Option A is invalid because keys cannot be exported and imported across regions. Option B is invalid because key rotation cannot be used to export keys

Option C is invalid because the backing key cannot be used to export keys This is mentioned in the AWS documentation

What geographic region are my keys stored in?

Keys are only stored and used in the region in which they are created. They cannot be transferred to another region. For example; keys created in the EU-Central (Frankfurt) region are only stored and used within the EU-Central (Frankfurt) region

For more information on KMS please visit the following URL: <https://aws.amazon.com/kms/faqs/>

The correct answer is: This is not possible since keys from KMS are region specific Submit your Feedback/Queries to our Experts

NEW QUESTION 46

You have a requirement to conduct penetration testing on the AWS Cloud for a couple of EC2 Instances. How could you go about doing this? Choose 2 right answers from the options given below. Please select:

- A. Get prior approval from AWS for conducting the test
- B. Use a pre-approved penetration testing tool.
- C. Work with an AWS partner and no need for prior approval request from AWS
- D. Choose any of the AWS instance type

Answer: AB

Explanation:

You can use a pre-approved solution from the AWS Marketplace. But till date the AWS Documentation still mentions that you have to get prior approval before conducting a test on the AWS Cloud for EC2 Instances.

Option C and D are invalid because you have to get prior approval first. AWS Docs Provides following details:

"For performing a penetration test on AWS resources first of all we need to take permission from AWS and complete a requisition form and submit it for approval. The form should contain information about the instances you wish to test identify the expected start and end dates/times of your test and requires you to read and agree to Terms and Conditions specific to penetration testing and to the use of appropriate tools for testing. Note that the end date may not be more than 90 days from the start date."

(
At this time, our policy does not permit testing small or micro RDS instance types. Testing of ml .small, t1 .micro or t2.nano EC2 instance types is not permitted.

For more information on penetration testing please visit the following URL: <https://aws.amazon.com/security/penetration-testing/>

The correct answers are: Get prior approval from AWS for conducting the test Use a pre-approved penetration testing tool. Submit your Feedback/Queries to our Experts

NEW QUESTION 47

Your company has created a set of keys using the AWS KMS service. They need to ensure that each key is only used for certain services. For example , they want one key to be used only for the S3 service. How can this be achieved? Please select:

- A. Create an IAM policy that allows the key to be accessed by only the S3 service.
- B. Create a bucket policy that allows the key to be accessed by only the S3 service.
- C. Use the kms:ViaService condition in the Key policy
- D. Define an IAM user, allocate the key and then assign the permissions to the required service

Answer: C

Explanation:

Option A and B are invalid because mapping keys to services cannot be done via either the IAM or bucket policy

Option D is invalid because keys for IAM users cannot be assigned to services This is mentioned in the AWS Documentation

The kms:ViaService condition key limits use of a customer-managed CMK to requests from particular AWS services. (AWS managed CMKs in your account, such as aws/s3, are always restricted to the AWS service that created them.)

For example, you can use kms:ViaService to allow a user to use a customer managed CMK only for requests that Amazon S3 makes on their behalf. Or you can use it to deny the user permission to a CMK when a request on their behalf comes from AWS Lambda.

For more information on key policy's for KMS please visit the following URL: <https://docs.aws.amazon.com/kms/latest/developerguide/policy-conditions.html>

The correct answer is: Use the kms:ViaService condition in the Key policy Submit your Feedback/Queries to our Experts

NEW QUESTION 51

You are planning on hosting a web application on AWS. You create an EC2 Instance in a public subnet. This instance needs to connect to an EC2 Instance that will host an Oracle database. Which of the following steps should be followed to ensure a secure setup is in place? Select 2 answers. Please select:

- A. Place the EC2 Instance with the Oracle database in the same public subnet as the Web server for faster communication
- B. Place the EC2 Instance with the Oracle database in a separate private subnet
- C. Create a database security group and ensure the web security group to allowed incoming access
- D. Ensure the database security group allows incoming traffic from 0.0.0.0/0

Answer: BC

Explanation:

The best secure option is to place the database in a private subnet. The below diagram from the AWS Documentation shows this setup. Also ensure that access is not allowed from all sources but just from the web servers.

Option A is invalid because databases should not be placed in the public subnet

Option D is invalid because the database security group should not allow traffic from the internet For more information on this type of setup, please refer to the below URL: https://docs.aws.amazon.com/AmazonVPC/latest/UserGuideA/PC_Scenario2.

The correct answers are: Place the EC2 Instance with the Oracle database in a separate private subnet Create a database security group and ensure the web security group to allowed incoming access

Submit your Feedback/Queries to our Experts

NEW QUESTION 56

A company hosts data in S3. There is now a mandate that going forward all data in the S3 bucket needs to encrypt at rest. How can this be achieved? Please select:

- A. Use AWS Access keys to encrypt the data
- B. Use SSL certificates to encrypt the data
- C. Enable server side encryption on the S3 bucket
- D. Enable MFA on the S3 bucket

Answer: C

Explanation:

The AWS Documentation mentions the following

Server-side encryption is about data encryption at rest—that is, Amazon S3 encrypts your data at the object level as it writes it to disks in its data centers and decrypts it for you when you access it. As long as you authenticate your request and you have access permissions, there is no difference in the way you access encrypted or unencrypted objects.

Options A and B are invalid because neither Access Keys nor SSL certificates can be used to encrypt data.

Option D is invalid because MFA is just used as an extra level of security for S3 buckets For more information on S3 server side encryption, please refer to the below Link: <https://docs.aws.amazon.com/AmazonS3/latest/dev/serv-side-encryption.html>

Submit your Feedback/Queries to our Experts

NEW QUESTION 57

One of your company's EC2 Instances have been compromised. The company has strict po thorough investigation on finding the culprit for the security breach. What would you do in from the options given below.

Please select:

- A. Take a snapshot of the EBS volume
- B. Isolate the machine from the network
- C. Make sure that logs are stored securely for auditing and troubleshooting purpose
- D. Ensure all passwords for all 1AM users are changed
- E. Ensure that all access kevs are rotate

Answer: ABC

Explanation:

Some of the important aspects in such a situation are

1) First isolate the instance so that no further security harm can occur on other AWS resources

2) Take a snapshot of the EBS volume for further investigation. This is incase if you need to shutdown the initial instance and do a separate investigation on the data

3) Next is Option C. This indicates that we have already got logs and we need to make sure that it is stored securely so that n unauthorised person can access it and manipulate it.

Option D and E are invalid because they could have adverse effects for the other 1AM users. For more information on adopting a security framework, please refer to below URL [https://d1 .awsstatic.com/whitepapers/compliance/NIST Cybersecurity Framework](https://d1.awsstatic.com/whitepapers/compliance/NIST%20Cybersecurity%20Framework.pdf)

Note:

In the question we have been asked to take actions to find the culprit and to help the investigation or to further reduce the damage that has happened due to the security breach. So by keeping logs secure is one way of helping the investigation.

The correct answers are: Take a snapshot of the EBS volume. Isolate the machine from the network. Make sure that logs are stored securely for auditing and troubleshooting purpose

Submit your Feedback/Queries to our Experts

NEW QUESTION 59

Your company hosts a large section of EC2 instances in AWS. There are strict security rules governing the EC2 Instances. During a potential security breach , you need to ensure quick investigation of the underlying EC2 Instance. Which of the following service can help you quickly provision a test environment to look into the breached instance.

Please select:

- A. AWS Cloudwatch
- B. AWS Cloudformation
- C. AWS Cloudtrail
- D. AWS Config

Answer: B

Explanation:

The AWS Security best practises mentions the following

Unique to AWS, security practitioners can use CloudFormation to quickly create a new, trusted environment in which to conduct deeper investigation. The CloudFormation template can preconfigure instances in an isolated environment that contains all the necessary tools forensic teams

need to determine the cause of the incident This cuts down on the time it takes to gather necessary tools, isolates systems under examination, and ensures that the team is operating in a clean room. Option A is incorrect since this is a logging service and cannot be used to provision a test environment

Option C is incorrect since this is an API logging service and cannot be used to provision a test environment

Option D is incorrect since this is a configuration service and cannot be used to provision a test environment

For more information on AWS Security best practises, please refer to below URL: <https://d1.awsstatic.com/whitepapers/architecture/AWS-Security-Pillar.pdf>

The correct answer is: AWS Cloudformation Submit your Feedback/Queries to our Experts

NEW QUESTION 63

Your company use AWS KMS for management of its customer keys. From time to time, there is a requirement to delete existing keys as part of housekeeping activities. What can be done during the deletion process to verify that the key is no longer being used.

Please select:

- A. Use CloudTrail to see if any KMS API request has been issued against existing keys
- B. Use Key policies to see the access level for the keys
- C. Rotate the keys once before deletion to see if other services are using the keys
- D. Change the 1AM policy for the keys to see if other services are using the keys

Answer: A

Explanation:

The AWS lentation mentions the following

You can use a combination of AWS CloudTrail, Amazon CloudWatch Logs, and Amazon Simple Notification Service (Amazon SNS) to create an alarm that notifies

you of AWS KMS API requests that attempt to use a customer master key (CMK) that is pending deletion. If you receive a notification from such an alarm, you might want to cancel deletion of the CMK to give yourself more time to determine whether you want to delete it
Options B and D are incorrect because Key policies nor 1AM policies can be used to check if the keys are being used.
Option C is incorrect since rotation will not help you check if the keys are being used. For more information on deleting keys, please refer to below URL:
<https://docs.aws.amazon.com/kms/latest/developereuide/deletine-keys-creatine-cloudwatchalarm.html>
The correct answer is: Use CloudTrail to see if any KMS API request has been issued against existing keys Submit your Feedback/Queries to our Experts

NEW QUESTION 64

A Devops team is currently looking at the security aspect of their CI/CD pipeline. They are making use of AWS resource? for their infrastructure. They want to ensure that the EC2 Instances don't have any high security vulnerabilities. They want to ensure a complete DevSecOps process. How can this be achieved? Please select:

- A. Use AWS Config to check the state of the EC2 instance for any sort of security issues.
- B. Use AWS Inspector API's in the pipeline for the EC2 Instances
- C. Use AWS Trusted Advisor API's in the pipeline for the EC2 Instances
- D. Use AWS Security Groups to ensure no vulnerabilities are present

Answer: B

Explanation:

Amazon Inspector offers a programmatic way to find security defects or misconfigurations in your operating systems and applications. Because you can use API calls to access both the processing of assessments and the results of your assessments, integration of the findings into workflow and notification systems is simple. DevOps teams can integrate Amazon Inspector into their CI/CD pipelines and use it to identify any pre-existing issues or when new issues are introduced. Option A.C and D are all incorrect since these services cannot check for Security Vulnerabilities. These can only be checked by the AWS Inspector service. For more information on AWS Security best practices, please refer to below URL: https://d1.awsstatic.com/whitepapers/Security/AWS_Security_Best_Practices.pdf
The correct answer is: Use AWS Inspector API's in the pipeline for the EC2 Instances Submit your Feedback/Queries to our Experts

NEW QUESTION 68

Your company has just started using AWS and created an AWS account. They are aware of the potential issues when root access is enabled. How can they best safeguard the account when it comes to root access? Choose 2 answers fro the options given below
Please select:

- A. Delete the root access account
- B. Create an Admin 1AM user with the necessary permissions
- C. Change the password for the root account.
- D. Delete the root access keys

Answer: BD

Explanation:

The AWS Documentation mentions the following
All AWS accounts have root user credentials (that is, the credentials of the account owner). These credentials allow full access to all resources in the account. Because you cant restrict permissions for root user credentials, we recommend that you delete your root user access keys. Then create AWS Identity and Access Management (1AM) user credentials for everyday interaction with AWS. Option A is incorrect since you cannot delete the root access account
Option C is partially correct but cannot be used as the ideal solution for safeguarding the account For more information on root access vs admin 1AM users, please refer to below URL: <https://docs.aws.amazon.com/eeneral/latest/er/root-vs-iam.html>
The correct answers are: Create an Admin 1AM user with the necessary permissions. Delete the root access keys Submit your Feedback/Queries to our Experts

NEW QUESTION 73

A company has hired a third-party security auditor, and the auditor needs read-only access to all AWS resources and logs of all VPC records and events that have occurred on AWS. How can the company meet the auditor's requirements without comprising security in the AWS environment? Choose the correct answer from the options below
Please select:

- A. Create a role that has the required permissions for the auditor.
- B. Create an SNS notification that sends the CloudTrail log files to the auditor's email when CloudTrail delivers the logs to S3, but do not allow the auditor access to the AWS environment.
- C. The company should contact AWS as part of the shared responsibility model, and AWS will grant required access to th^ third-party auditor.
- D. Enable CloudTrail logging and create an 1AM user who has read-only permissions to the required AWS resources, including the bucket containing the CloudTrail logs.

Answer: D

Explanation:

AWS CloudTrail is a service that enables governance, compliance, operational auditing, and risk auditing of your AWS account. With CloudTrail, you can log, continuously monitor, and retain events related to API calls across your AWS infrastructure. CloudTrail provides a history of AWS API calls for your account including API calls made through the AWS Management Console, AWS SDKs, command line tools, and other AWS services. This history simplifies security analysis, resource change tracking, and troubleshooting.
Option A and C are incorrect since Cloudtrail needs to be used as part of the solution Option B is incorrect since the auditor needs to have access to Cloudtrail For more information on cloudtrail, please visit the below URL: <https://aws.amazon.com/cloudtrail>
The correct answer is: Enable CloudTrail logging and create an 1AM user who has read-only permissions to the required AWS resources, including the bucket containing the CloudTrail logs. Submit your Feedback/Queries to our Experts

NEW QUESTION 76

An auditor needs access to logs that record all API events on AWS. The auditor only needs read-only access to the log files and does not need access to each AWS account. The company has multiple AWS accounts, and the auditor needs access to all the logs for all the accounts. What is the best way to configure access for the auditor to view event logs from all accounts? Choose the correct answer from the options below
Please select:

- A. Configure the CloudTrail service in each AWS account, and have the logs delivered to an AWS bucket on each account, while granting the auditor permissions to the bucket via roles in the secondary accounts and a single primary IAM account that can assume a read-only role in the secondary AWS accounts.
- B. Configure the CloudTrail service in the primary AWS account and configure consolidated billing for all the secondary account
- C. Then grant the auditor access to the S3 bucket that receives the CloudTrail log files.
- D. Configure the CloudTrail service in each AWS account and enable consolidated logging inside of CloudTrail.
- E. Configure the CloudTrail service in each AWS account and have the logs delivered to a single AWS bucket in the primary account and grant the auditor access to that single bucket in the primary account

Answer: D

Explanation:

Given the current requirements, assume the method of "least privilege" security design and only allow the auditor access to the minimum amount of AWS resources as possible

AWS CloudTrail is a service that enables governance, compliance, operational auditing, and risk auditing of your AWS account. With CloudTrail, you can log, continuously monitor, and retain events related to API calls across your AWS infrastructure. CloudTrail provides a history of AWS API calls for your account including API calls made through the AWS Management Console, AWS SDKs, command line tools, and other AWS services. This history simplifies security analysis, resource change tracking, and troubleshooting

only be granted access in one location

Option A is incorrect since the auditor should only be granted access in one location B is incorrect since consolidated billing is not a key requirement as part of the question

Option C is incorrect since there is not consolidated logging

For more information on Cloudtrail please refer to the below URL: <https://aws.amazon.com/cloudtrail>

(

The correct answer is: Configure the CloudTrail service in each AWS account and have the logs delivered to a single AWS bucket in the primary account and grant the auditor access to that single bucket in the primary account.

Submit your Feedback/Queries to our Experts

NEW QUESTION 78

You have several S3 buckets defined in your AWS account. You need to give access to external AWS accounts to these S3 buckets. Which of the following can allow you to define the permissions for the external accounts? Choose 2 answers from the options given below

Please select:

- A. IAM policies
- B. Buckets ACL's
- C. IAM users
- D. Bucket policies

Answer: BD

Explanation:

The AWS Security whitepaper gives the type of access control and to what level the control can be given

Options A and C are incorrect since for external access to buckets, you need to use either Bucket policies or Bucket ACL's or more information on Security for storage services role please refer to the below URL:

<https://d1.awsstatic.com/whitepapers/Security/Security Storage Services Whitepaper.pdf> The correct answers are: Buckets ACL's, Bucket policies

Submit your Feedback/Queries to our Experts

NEW QUESTION 83

You are planning on using the AWS KMS service for managing keys for your application. For which of the following can the KMS CMK keys be used for encrypting? Choose 2 answers from the options given below

Please select:

- A. Image Objects
- B. Large files
- C. Password
- D. RSA Keys

Answer: CD

Explanation:

The CMK keys themselves can only be used for encrypting data that is maximum 4KB in size. Hence it can be used for encrypting information such as passwords and RSA keys.

Option A and B are invalid because the actual CMK key can only be used to encrypt small amounts of data and not large amounts of data

A\ You have to generate the data key from the CMK key in order to

encrypt high amounts of data

For more information on the concepts for KMS, please visit the following URL: <https://docs.aws.amazon.com/kms/latest/developerguide/concepts.html>

The correct answers are: Password, RSA Keys Submit your Feedback/Queries to our Experts

NEW QUESTION 88

A company has been using the AWS KMS service for managing its keys. They are planning on carrying out housekeeping activities and deleting keys which are no longer in use. What are the ways that can be incorporated to see which keys are in use? Choose 2 answers from the options given below

Please select:

- A. Determine the age of the master key
- B. See who is assigned permissions to the master key
- C. See Cloudtrail for usage of the key
- D. Use AWS cloudwatch events for events generated for the key

Answer: BC

Explanation:

The direct ways that can be used to see how the key is being used is to see the current access permissions and cloudtrail logs

Option A is invalid because seeing how long ago the key was created would not determine the usage of the key

Option D is invalid because Cloudtrail Event is better for seeing for events generated by the key This is also mentioned in the AWS Documentation

Examining CMK Permissions to Determine the Scope of Potential Usage

Determining who or what currently has access to a customer master key (CMK) might help you determine how widely the CM was used and whether it is still needed. To learn how to determine who or what currently has access to a CMK, go to Determining Access to an AWS KMS Customer Master Key.

Examining AWS CloudTrail Logs to Determine Actual Usage

AWS KMS is integrated with AWS CloudTrail, so all AWS KMS API activity is recorded in CloudTrail log files. If you have CloudTrail turned on in the region where your customer master key (CMK) is

located, you can examine your CloudTrail log files to view a history of all AWS KMS API activity for a particular CMK, and thus its usage history. You might be able to use a CMK's usage history to help you determine whether or not you still need it

For more information on determining the usage of CMK keys, please visit the following URL: <https://docs.aws.amazon.com/kms/latest/developerguide/deleting-keys-determining-usage.html>

The correct answers are: See who is assigned permissions to the master key. See Cloudtrail for usage of the key Submit your Feedback/Queries to our Experts

NEW QUESTION 90

Your company has been using AWS for the past 2 years. They have separate S3 buckets for logging the various AWS services that have been used. They have hired an external vendor for analyzing their log files. They have their own AWS account. What is the best way to ensure that the partner account can access the log files in the company account for analysis. Choose 2 answers from the options given below

Please select:

- A. Create an IAM user in the company account
- B. Create an IAM Role in the company account
- C. Ensure the IAM user has access for read-only to the S3 buckets
- D. Ensure the IAM Role has access for read-only to the S3 buckets

Answer: BD

Explanation:

The AWS Documentation mentions the following

To share log files between multiple AWS accounts, you must perform the following general steps. These steps are explained in detail later in this section.

Create an IAM role for each account that you want to share log files with.

For each of these IAM roles, create an access policy that grants read-only access to the account you want to share the log files with.

Have an IAM user in each account programmatically assume the appropriate role and retrieve the log files.

Options A and C are invalid because creating an IAM user and then sharing the IAM user credentials with the vendor is a direct 'NO' practise from a security perspective.

For more information on sharing cloudtrail logs files, please visit the following URL <https://docs.aws.amazon.com/awscloudtrail/latest/userguide/cloudtrail-share-logs.html>

The correct answers are: Create an IAM Role in the company account Ensure the IAM Role has access for read-only to the S3 buckets

Submit your Feedback/Queries to our Experts

NEW QUESTION 91

A company hosts critical data in an S3 bucket. Even though they have assigned the appropriate permissions to the bucket, they are still worried about data deletion. What measures can be taken to restrict the risk of data deletion on the bucket. Choose 2 answers from the options given below Please select:

- A. Enable versioning on the S3 bucket
- B. Enable data at rest for the objects in the bucket
- C. Enable MFA Delete in the bucket policy
- D. Enable data in transit for the objects in the bucket

Answer: AC

Explanation:

One of the AWS Security blogs mentions the following

Versioning keeps multiple versions of an object in the same bucket. When you enable it on a bucket Amazon S3 automatically adds a unique version ID to every object stored in the bucket. At that point, a simple DELETE action does not permanently delete an object version; it merely associates a delete marker with the object. If you want to permanently delete an object version, you must specify its version ID in your DELETE request.

You can add another layer of protection by enabling MFA Delete on a versioned bucket. Once you do so, you must provide your AWS accounts access keys and a valid code from the account's MFA device in order to permanently delete an object version or suspend or reactivate versioning on the bucket. Option B is invalid because enabling encryption does not guarantee risk of data deletion.

Option D is invalid because this option does not guarantee risk of data deletion.

For more information on AWS S3 versioning and MFA please refer to the below URL: <https://aws.amazon.com/blogs/security/securing-access-to-aws-using-mfa-part-3/>

NEW QUESTION 95

You are designing a connectivity solution between on-premises infrastructure and Amazon VPC. Your server's on-premises will be communicating with your VPC instances. You will be establishing IPSec

tunnels over the internet. You will be using VPN gateways and terminating the IPsec tunnels on AWSsupported customer gateways. Which of the following objectives would you achieve by

implementing an IPSec tunnel as outlined above? Choose 4 answers from the options below Please select:

- A. End-to-end protection of data in transit
- B. End-to-end Identity authentication
- C. Data encryption across the internet
- D. Protection of data in transit over the Internet
- E. Peer identity authentication between VPN gateway and customer gateway
- F. Data integrity protection across the Internet

Answer: CDEF

Explanation:

Since the Web server needs to talk to the database server on port 3306 that means that the database server should allow incoming traffic on port 3306. The below table from the aws documentation shows how the security groups should be set up.

Option B is invalid because you need to allow incoming access for the database server from the WebSecGrp security group.

Options C and D are invalid because you need to allow Outbound traffic and not inbound traffic For more information on security groups please visit the below

Link: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Scenario2.html

The correct answer is: Allow Inbound on port 3306 for Source Web Server Security Group WebSecGrp. Submit your Feedback/Queries to our Experts

NEW QUESTION 97

You are planning to use AWS Config to check the configuration of the resources in your AWS account. You are planning on using an existing IAM role and using it for the AWS Config resource. Which of the following is required to ensure the AWS config service can work as required?

Please select:

- A. Ensure that there is a trust policy in place for the AWS Config service within the role
- B. Ensure that there is a grant policy in place for the AWS Config service within the role
- C. Ensure that there is a user policy in place for the AWS Config service within the role
- D. Ensure that there is a group policy in place for the AWS Config service within the role

Answer: A

Explanation:

Options B,C and D are invalid because you need to ensure a trust policy is in place and not a grant, user or group policy or more information on the IAM role permissions please visit the below Link: <https://docs.aws.amazon.com/config/latest/developerguide/iamrole-permissions.html>

The correct answer is: Ensure that there is a trust policy in place for the AWS Config service within the role

Submit your Feedback/Queries to our Experts

NEW QUESTION 99

An organization has setup multiple IAM users. The organization wants that each IAM user accesses the IAM console only within the organization and not from outside. How can it achieve this? Please select:

- A. Create an IAM policy with the security group and use that security group for AWS console login
- B. Create an IAM policy with a condition which denies access when the IP address range is not from the organization
- C. Configure the EC2 instance security group which allows traffic only from the organization's IP range
- D. Create an IAM policy with VPC and allow a secure gateway between the organization and AWS Console

Answer: B

Explanation:

You can actually use a Deny condition which will not allow the person to log in from outside. The below example shows the Deny condition to ensure that any address specified in the source address is not allowed to access the resources in aws.

Option A is invalid because you don't mention the security group in the IAM policy Option C is invalid because security groups by default don't allow traffic

Option D is invalid because the IAM policy does not have such an option For more information on IAM policy conditions, please visit the URL:

http://docs.aws.amazon.com/IAM/latest/UserGuide/access_pol_examples.htm#iam-policy-example-ec2-two-condition!

The correct answer is: Create an IAM policy with a condition which denies access when the IP address range is not from the organization

Submit your Feedback/Queries to our Experts

NEW QUESTION 103

A company has a requirement to create a DynamoDB table. The company's software architect has provided the following CLI command for the DynamoDB table

Which of the following has been taken of from a security perspective from the above command? Please select:

- A. Since the ID is hashed, it ensures security of the underlying table.
- B. The above command ensures data encryption at rest for the Customer table
- C. The above command ensures data encryption in transit for the Customer table
- D. The right throughput has been specified from a security perspective

Answer: B

Explanation:

The above command with the "-sse-specification Enabled=true" parameter ensures that the data for the DynamoDB table is encrypted at rest.

Options A,C and D are all invalid because this command is specifically used to ensure data encryption at rest

For more information on DynamoDB encryption, please visit the URL:

<https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/encryption.tutorial.html> The correct answer is: The above command ensures data encryption at rest for the Customer table

NEW QUESTION 106

In your LAMP application, you have some developers that say they would like access to your logs. However, since you are using an AWS Auto Scaling group, your instances are constantly being recreated.

What would you do to make sure that these developers can access these log files? Choose the correct answer from the options below

Please select:

- A. Give only the necessary access to the Apache servers so that the developers can gain access to the log files.
- B. Give root access to your Apache servers to the developers.
- C. Give read-only access to your developers to the Apache servers.
- D. Set up a central logging server that you can use to archive your logs; archive these logs to an S3 bucket for developer-access.

Answer: D

Explanation:

One important security aspect is to never give access to actual servers, hence Option A,B and C are just totally wrong from a security perspective.

The best option is to have a central logging server that can be used to archive logs. These logs can then be stored in S3.

Options A,B and C are all invalid because you should not give access to the developers on the Apache servers

For more information on S3, please refer to the below link <https://aws.amazon.com/documentation/s3>

The correct answer is: Set up a central logging server that you can use to archive your logs; archive these logs to an S3 bucket for developer-access.

Submit your Feedback/Queries to our Experts

NEW QUESTION 107

Your company is planning on developing an application in AWS. This is a web based application. The application users will use their facebook or google identities for authentication. You want to have the ability to manage user profiles without having to add extra coding to manage this. Which of the below would assist in this. Please select:

- A. Create an OIDC identity provider in AWS
- B. Create a SAML provider in AWS
- C. Use AWS Cognito to manage the user profiles
- D. Use IAM users to manage the user profiles

Answer: B

Explanation:

The AWS Documentation mentions the following The AWS Documentation mentions the following
OIDC identity providers are entities in IAM that describe an identity provider (IdP) service that supports the OpenID Connect (OIDC) standard. You use an OIDC identity provider when you want to establish trust between an OIDC-compatible IdP—such as Google, Salesforce, and many others—and your AWS account This is useful if you are creating a mobile app or web application that requires access to AWS resources, but you don't want to create custom sign-in code or manage your own user identities

Option A is invalid because in the security groups you would not mention this information/ Option C is invalid because SAML is used for federated authentication

Option D is invalid because you need to use the OIDC identity provider in AWS For more information on ODIC identity providers, please refer to the below Link:

https://docs.aws.amazon.com/IAM/latest/UserGuide/id_roles_providers_create_oidc.html The correct answer is: Create an OIDC identity provider in AWS

NEW QUESTION 112

Your company is planning on developing an application in AWS. This is a web based application. The application user will use their facebook or google identities for authentication. You want to have the ability to manage user profiles without having to add extra coding to manage this. Which of the below would assist in this. Please select:

- A. Create an OIDC identity provider in AWS
- B. Create a SAML provider in AWS
- C. Use AWS Cognito to manage the user profiles
- D. Use IAM users to manage the user profiles

Answer: C

Explanation:

The AWS Documentation mentions the following

A user pool is a user directory in Amazon Cognito. With a user pool, your users can sign in to your web or mobile app through Amazon Cognito. Your users can also sign in through social identity providers like Facebook or Amazon, and through SAML identity providers. Whether your users sign in directly or through a third party, all members of the user pool have a directory profile that you can access through an SDK.

User pools provide:

Sign-up and sign-in services.

A built-in, customizable web UI to sign in users.

Social sign-in with Facebook, Google, and Login with Amazon, as well as sign-in with SAML identity providers from your user pool.

User directory management and user profiles.

Security features such as multi-factor authentication (MFA), checks for compromised credentials, account takeover protection, and phone and email verification.

Customized workflows and user migration through AWS Lambda triggers. Options A and B are invalid because these are not used to manage users Option D is invalid because this would be a maintenance overhead

For more information on Cognito User Identity pools, please refer to the below Link: <https://docs.aws.amazon.com/coenito/latest/developerguide/cognito-user-identity-pools.html>

The correct answer is: Use AWS Cognito to manage the user profiles Submit your Feedback/Queries to our Experts

NEW QUESTION 113

Your company has many AWS accounts defined and all are managed via AWS Organizations. One AWS account has a S3 bucket that has critical dat

A. How can we ensure that all the users in the AWS organisation have access to this bucket? Please select:

- B. Ensure the bucket policy has a condition which involves aws:PrincipalOrgID
- C. Ensure the bucket policy has a condition which involves aws:AccountNumber
- D. Ensure the bucket policy has a condition which involves aws:PrincipalID
- E. Ensure the bucket policy has a condition which involves aws:OrgID

Answer: A

Explanation:

The AWS Documentation mentions the following

AWS Identity and Access Management (IAM) now makes it easier for you to control access to your AWS resources by using the AWS organization of IAM principals (users and roles). For some services, you grant permissions using resource-based policies to specify the accounts and principals that can access the resource and what actions they can perform on it. Now, you can use a new condition key, aws:PrincipalOrgID, in these policies to require all principals accessing the resource to be from an account in the organization

Option B.C and D are invalid because the condition in the bucket policy has to mention aws:PrincipalOrgID

For more information on controlling access via Organizations, please refer to the below Link: <https://aws.amazon.com/blogs/security/control-access-to-aws-resources-by-usins-the-awsorganization- of-iam-principal>

(

The correct answer is: Ensure the bucket policy has a condition which involves aws:PrincipalOrgID Submit your Feedback/Queries to our Experts

NEW QUESTION 114

Your organization is preparing for a security assessment of your use of AWS. In preparation for this assessment, which three IAM best practices should you consider implementing?

Please select:

- A. Create individual IAM users
- B. Configure MFA on the root account and for privileged IAM users
- C. Assign IAM users and groups configured with policies granting least privilege access
- D. Ensure all users have been assigned and are frequently rotating a password, access ID/secret key, and X.509 certificate

Answer: ABC

Explanation:

When you go to the security dashboard, the security status will show the best practices for initiating the first level of security.

Option D is invalid because as per the dashboard, this is not part of the security recommendation For more information on best security practices please visit the

URL: <https://aws.amazon.com/whitepapers/aws-security-best-practices>;

The correct answers are: Create individual 1AM users, Configure MFA on the root account and for privileged 1AM users. Assign 1AM users and groups configured with policies granting least privilege access

Submit your Feedback/Queries to our Experts

NEW QUESTION 117

You have a set of 100 EC2 Instances in an AWS account. You need to ensure that all of these instances are patched and kept to date. All of the instances are in a private subnet. How can you achieve this. Choose 2 answers from the options given below

Please select:

- A. Ensure a NAT gateway is present to download the updates
- B. Use the Systems Manager to patch the instances
- C. Ensure an internet gateway is present to download the updates
- D. Use the AWS inspector to patch the updates

Answer: AB

Explanation:

Option C is invalid because the instances need to remain in the private: Option D is invalid because AWS inspector can only detect the patches

One of the AWS Blogs mentions how patching of Linux servers can be accomplished. Below is the diagram representation of the architecture setup

For more information on patching Linux workloads in AWS, please refer to the Lin. <https://aws.amazon.com/blogs/security/how-to-patch-linux-workloads-on-aws/>

The correct answers are: Ensure a NAT gateway is present to download the updates. Use the Systems Manager to patch the instances

Submit your Feedback/Queries to our Experts

NEW QUESTION 120

Your company looks at the gaming domain and hosts several Ec2 Instances as game servers. The servers each experience user loads in the thousands. There is a concern of DDos attacks on the EC2 Instances which could cause a huge revenue loss to the company. Which of the following can help mitigate this security concern and also ensure minimum downtime for the servers.

Please select:

- A. Use VPC Flow logs to monitor the VPC and then implement NACL's to mitigate attacks
- B. Use AWS Shield Advanced to protect the EC2 Instances
- C. Use AWS Inspector to protect the EC2 Instances
- D. Use AWS Trusted Advisor to protect the EC2 Instances

Answer: B

Explanation:

Below is an excerpt from the AWS Documentation on some of the use cases for AWS Shield

NEW QUESTION 125

You currently operate a web application In the AWS US-East region. The application runs on an autoscaled layer of EC2 instances and an RDS Multi-AZ database. Your IT security compliance officer has

tasked you to develop a reliable and durable logging solution to track changes made to your EC2.IAM and RDS resources. The solution must ensure the integrity

and confidentiality of your log dat

- A. Which of these solutions would you recommend? Please select:
- B. Create a new CloudTrail trail with one new S3 bucket to store the logs and with the global services option selecte
- C. Use 1AM roles S3 bucket policies and Mufti Factor Authentication (MFA) Delete on the S3 bucket that stores your logs.
- D. Create a new CloudTrail with one new S3 bucket to store the log
- E. Configure SNS to send log file delivery notifications to your management syste
- F. Use 1AM roles and S3 bucket policies on the S3 bucket that stores your logs.
- G. Create a new CloudTrail trail with an existing S3 bucket to store the logs and with the global services option selecte
- H. Use S3 ACLsand Multi Factor Authentication (MFA) Delete on the S3 bucket that stores your logs.
- I. Create three new CloudTrail trails with three new S3 buckets to store the logs one for the AWS Management console, one for AWS SDKs and one for command line tool
- J. Use 1AM roles and S3 bucket policies on the S3 buckets that store your logs.

Answer: A

Explanation:

AWS Identity and Access Management (IAM) is integrated with AWS CloudTrail, a service that logs AWS events made by or on behalf of your AWS account. CloudTrail logs authenticated AWS API calls and also AWS sign-in events, and collects this event information in files that are delivered to Amazon S3 buckets. You need to ensure that all services are included. Hence option B is partially correct. Option B is invalid because you need to ensure that global services is select Option C is invalid because you should use bucket policies Option D is invalid because you should ideally just create one S3 bucket For more information on Cloudtrail, please visit the below URL: <http://docs.aws.amazon.com/IAM/latest/UserGuide/cloudtrail-inteeration.html> The correct answer is: Create a new CloudTrail trail with one new S3 bucket to store the logs and with the global services o selected. Use 1AM roles S3 bucket policies and Mulrj Factor Authentication (MFA) Delete on the S3 bucket that stores your l(Submit your Feedback/Queries to our Experts

NEW QUESTION 129

You work at a company that makes use of AWS resources. One of the key security policies is to ensure that all data i encrypted both at rest and in transit. Which of the following is one of the right ways to implement this.

Please select:

- A. Use S3 SSE and use SSL for data in transit
- B. SSL termination on the ELB
- C. Enabling Proxy Protocol
- D. Enabling sticky sessions on your load balancer

Answer: A

Explanation:

By disabling SSL termination, you are leaving an unsecure connection from the ELB to the back end instances. Hence this means that part of the data transit is not being encrypted. Option B is incorrect because this would not guarantee complete encryption of data in transit Option C and D are incorrect because these would not guarantee encryption For more information on SSL Listeners for your load balancer, please visit the below URL: <http://docs.aws.amazon.com/elasticloadbalancine/latest/classic/elb-https-load-balancers.html> The correct answer is: Use S3 SSE and use SSL for data in transit Submit your Feedback/Queries to our Experts

NEW QUESTION 133

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

AWS-Certified-Security-Specialty Practice Exam Features:

- * AWS-Certified-Security-Specialty Questions and Answers Updated Frequently
- * AWS-Certified-Security-Specialty Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Certified-Security-Specialty Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AWS-Certified-Security-Specialty Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The AWS-Certified-Security-Specialty Practice Test Here](#)