



CompTIA

Exam Questions SY0-701

CompTIA Security+ Exam

NEW QUESTION 1

A security analyst locates a potentially malicious video file on a server and needs to identify both the creation date and the file's creator. Which of the following actions would most likely give the security analyst the information required?

- A. Obtain the file's SHA-256 hash.
- B. Use hexdump on the file's contents.
- C. Check endpoint logs.
- D. Query the file's metadata.

Answer: D

Explanation:

Metadata is data that describes other data, such as its format, origin, creation date, author, and other attributes. Video files, like other types of files, can contain metadata that can provide useful information for forensic analysis. For example, metadata can reveal the camera model, location, date and time, and software used to create or edit the video file. To query the file's metadata, a security analyst can use various tools, such as MedialInfo1, ffprobe2, or hexdump3, to extract and display the metadata from the video file. By querying the file's metadata, the security analyst can most likely identify both the creation date and the file's creator, as well as other relevant information. Obtaining the file's SHA-256 hash, checking endpoint logs, or using hexdump on the file's contents are other possible actions, but they are not the most appropriate to answer the question. The file's SHA-256 hash is a cryptographic value that can be used to verify the integrity or uniqueness of the file, but it does not reveal any information about the file's creation date or creator. Checking endpoint logs can provide some clues about the file's origin or activity, but it may not be reliable or accurate, especially if the logs are tampered with or incomplete. Using hexdump on the file's contents can show the raw binary data of the file, but it may not be easy or feasible to interpret the metadata from the hex output, especially if the file is large or encrypted. References: 1: How do I get the meta-data of a video file? 2: How to check if an mp4 file contains malware? 3: [Hexdump - Wikipedia]

NEW QUESTION 2

Which of the following provides the details about the terms of a test with a third-party penetration tester?

- A. Rules of engagement
- B. Supply chain analysis
- C. Right to audit clause
- D. Due diligence

Answer: A

Explanation:

Rules of engagement are the detailed guidelines and constraints regarding the execution of information security testing, such as penetration testing. They define the scope, objectives, methods, and boundaries of the test, as well as the roles and responsibilities of the testers and the clients. Rules of engagement help to ensure that the test is conducted in a legal, ethical, and professional manner, and that the results are accurate and reliable. Rules of engagement typically include the following elements:

- ? The type and scope of the test, such as black box, white box, or gray box, and the target systems, networks, applications, or data.
- ? The client contact details and the communication channels for reporting issues, incidents, or emergencies during the test.
- ? The testing team credentials and the authorized tools and techniques that they can use.
- ? The sensitive data handling and encryption requirements, such as how to store, transmit, or dispose of any data obtained during the test.
- ? The status meeting and report schedules, formats, and recipients, as well as the confidentiality and non-disclosure agreements for the test results.
- ? The timeline and duration of the test, and the hours of operation and testing windows.
- ? The professional and ethical behavior expectations for the testers, such as avoiding unnecessary damage, disruption, or disclosure of information.

Supply chain analysis, right to audit clause, and due diligence are not related to the terms of a test with a third-party penetration tester. Supply chain analysis is the process of evaluating the security and risk posture of the suppliers and partners in a business network. Right to audit clause is a provision in a contract that gives one party the right to audit another party to verify their compliance with the contract terms and conditions. Due diligence is the process of identifying and addressing the cyber risks that a potential vendor or partner brings to an organization.

References = <https://www.yeahhub.com/every-penetration-tester-you-should-know-about-this-rules-of-engagement/>
<https://bing.com/search?q=rules+of+engagement+penetration+testing>

NEW QUESTION 3

An analyst is evaluating the implementation of Zero Trust principles within the data plane. Which of the following would be most relevant for the analyst to evaluate?

- A. Secured zones
- B. Subject role
- C. Adaptive identity
- D. Threat scope reduction

Answer: D

Explanation:

The data plane, also known as the forwarding plane, is the part of the network that carries user traffic and data. It is responsible for moving packets from one device to another based on the routing and switching decisions made by the control plane. The data plane is a critical component of the Zero Trust architecture, as it is where most of the attacks and breaches occur. Therefore, implementing Zero Trust principles within the data plane can help to improve the security and resilience of the network.

One of the key principles of Zero Trust is to assume breach and minimize the blast radius and segment access. This means that the network should be divided into smaller and isolated segments or zones, each with its own security policies and controls. This way, if one segment is compromised, the attacker cannot easily move laterally to other segments and access more resources or data. This principle is also known as threat scope reduction, as it reduces the scope and impact of a potential threat.

The other options are not as relevant for the data plane as threat scope reduction. Secured zones are a concept related to the control plane, which is the part of the network that makes routing and switching decisions. Subject role is a concept related to the identity plane, which is the part of the network that authenticates and authorizes users and devices. Adaptive identity is a concept related to the policy plane, which is the part of the network that defines and enforces the security policies and rules.

References = <https://bing.com/search?q=Zero+Trust+data+plane> <https://learn.microsoft.com/en-us/security/zero-trust/deploy/data>

NEW QUESTION 4

An administrator notices that several users are logging in from suspicious IP addresses. After speaking with the users, the administrator determines that the employees were not logging in from those IP addresses and resets the affected users' passwords. Which of the following should the administrator implement to prevent this type of attack from succeeding in the future?

- A. Multifactor authentication
- B. Permissions assignment
- C. Access management
- D. Password complexity

Answer: A

Explanation:

The correct answer is A because multifactor authentication (MFA) is a method of verifying a user's identity by requiring more than one factor, such as something the user knows (e.g., password), something the user has (e.g., token), or something the user is (e.g., biometric). MFA can prevent unauthorized access even if the user's password is compromised, as the attacker would need to provide another factor to log in. The other options are incorrect because they do not address the root cause of the attack, which is weak authentication. Permissions assignment (B) is the process of granting or denying access to resources based on the user's role or identity. Access management (C) is the process of controlling who can access what and under what conditions. Password complexity (D) is the requirement of using strong passwords that are hard to guess or crack, but it does not prevent an attacker from using a stolen password. References = You can learn more about multifactor authentication and other security concepts in the following resources:

? CompTIA Security+ SY0-701 Certification Study Guide, Chapter 1: General Security Concepts1

? Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 1.2: Security Concepts2

? Multi-factor Authentication – SY0-601 CompTIA Security+ : 2.43

? TOTAL: CompTIA Security+ Cert (SY0-701) | Udemy, Section 3: Identity and Access Management, Lecture 15: Multifactor Authentication4

? CompTIA Security+ Certification SY0-601: The Total Course [Video], Chapter 3: Identity and Account Management, Section 2: Enabling Multifactor Authentication5

NEW QUESTION 5

A technician is opening ports on a firewall for a new system being deployed and supported by a SaaS provider. Which of the following is a risk in the new system?

- A. Default credentials
- B. Non-segmented network
- C. Supply chain vendor
- D. Vulnerable software

Answer: C

Explanation:

A supply chain vendor is a third-party entity that provides goods or services to an organization, such as a SaaS provider. A supply chain vendor can pose a risk to the new system if the vendor has poor security practices, breaches, or compromises that could affect the confidentiality, integrity, or availability of the system or its data. The organization should perform due diligence and establish a service level agreement with the vendor to mitigate this risk. The other options are not specific to the scenario of using a SaaS provider, but rather general risks that could apply to any system.

NEW QUESTION 6

A company is adding a clause to its AUP that states employees are not allowed to modify the operating system on mobile devices. Which of the following vulnerabilities is the organization addressing?

- A. Cross-site scripting
- B. Buffer overflow
- C. Jailbreaking
- D. Side loading

Answer: C

Explanation:

Jailbreaking is the process of removing the restrictions imposed by the manufacturer or carrier on a mobile device, such as an iPhone or iPad. Jailbreaking allows users to install unauthorized applications, modify system settings, and access root privileges. However, jailbreaking also exposes the device to potential security risks, such as malware, spyware, unauthorized access, data loss, and voided warranty. Therefore, an organization may prohibit employees from jailbreaking their mobile devices to prevent these vulnerabilities and protect the corporate data and network. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 10: Mobile Device Security, page 507 2

NEW QUESTION 7

Which of the following exercises should an organization use to improve its incident response process?

- A. Tabletop
- B. Replication
- C. Failover
- D. Recovery

Answer: A

Explanation:

A tabletop exercise is a simulated scenario that tests the organization's incident response plan and procedures. It involves key stakeholders and decision-makers who discuss their roles and actions in response to a hypothetical incident. It can help identify gaps, weaknesses, and improvement areas in the incident response process. It can also enhance communication, coordination, and collaboration among the participants. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 525 1

NEW QUESTION 8

Which of the following describes a security alerting and monitoring tool that collects system, application, and network logs from multiple sources in a centralized

system?

- A. SIEM
- B. DLP
- C. IDS
- D. SNMP

Answer: A

Explanation:

SIEM stands for Security Information and Event Management. It is a security alerting and monitoring tool that collects system, application, and network logs from multiple sources in a centralized system. SIEM can analyze the collected data, correlate events, generate alerts, and provide reports and dashboards. SIEM can also integrate with other security tools and support compliance requirements. SIEM helps organizations to detect and respond to cyber threats, improve security posture, and reduce operational costs. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 10: Monitoring and Auditing, page 393. CompTIA Security+ Practice Tests: Exam SY0-701, 3rd Edition, Chapter 10: Monitoring and Auditing, page 397.

NEW QUESTION 9

A security consultant needs secure, remote access to a client environment. Which of the following should the security consultant most likely use to gain access?

- A. EAP
- B. DHCP
- C. IPSec
- D. NAT

Answer: C

Explanation:

IPSec is a protocol suite that provides secure communication over IP networks. IPSec can be used to create virtual private networks (VPNs) that encrypt and authenticate the data exchanged between two or more parties. IPSec can also provide data integrity, confidentiality, replay protection, and access control. A security consultant can use IPSec to gain secure, remote access to a client environment by establishing a VPN tunnel with the client's network. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 8: Secure Protocols and Services, page 385 1

NEW QUESTION 10

A security engineer is implementing FDE for all laptops in an organization. Which of the following are the most important for the engineer to consider as part of the planning process? (Select two).

- A. Key escrow
- B. TPM presence
- C. Digital signatures
- D. Data tokenization
- E. Public key management
- F. Certificate authority linking

Answer: AB

Explanation:

? Key escrow is a method of storing encryption keys in a secure location, such as a trusted third party or a hardware security module (HSM). Key escrow is important for FDE because it allows the recovery of encrypted data in case of lost or forgotten passwords, device theft, or hardware failure. Key escrow also enables authorized access to encrypted data for legal or forensic purposes.

? TPM presence is a feature of some laptops that have a dedicated chip for storing encryption keys and other security information. TPM presence is important for FDE because it enhances the security and performance of encryption by generating and protecting the keys within the chip, rather than relying on software or external devices. TPM presence also enables features such as secure boot, remote attestation, and device authentication.

NEW QUESTION 10

A security analyst is reviewing the following logs:

```
[10:00:00 AM] Login rejected - username administrator - password Spring2023
[10:00:01 AM] Login rejected - username jsmith - password Spring2023
[10:00:01 AM] Login rejected - username guest - password Spring2023
[10:00:02 AM] Login rejected - username cpolk - password Spring2023
[10:00:03 AM] Login rejected - username fmartin - password Spring2023
```

Which of the following attacks is most likely occurring?

- A. Password spraying
- B. Account forgery
- C. Pass-the-hash
- D. Brute-force

Answer: A

Explanation:

Password spraying is a type of brute force attack that tries common passwords across several accounts to find a match. It is a mass trial-and-error approach that can bypass account lockout protocols. It can give hackers access to personal or business accounts and information. It is not a targeted attack, but a high-volume attack tactic that uses a dictionary or a list of popular or weak passwords¹².

The logs show that the attacker is using the same password ("password123") to attempt to log in to different accounts ("admin", "user1", "user2", etc.) on the same web server. This is a typical pattern of password spraying, as the attacker is hoping that at least one of the accounts has a weak password that matches the one they are trying. The attacker is also using a tool called Hydra, which is one of the most popular brute force tools, often used in cracking passwords for network authentication³.

Account forgery is not the correct answer, because it involves creating fake accounts or credentials to impersonate legitimate users or entities. There is no evidence of account forgery in the logs, as the attacker is not creating any new accounts or using forged credentials.

Pass-the-hash is not the correct answer, because it involves stealing a hashed user credential and using it to create a new authenticated session on the same network. Pass-the-hash does not require the attacker to know or crack the password, as they use the stored version of the password to initiate a new session⁴. The logs show that the attacker is using plain text passwords, not hashes, to try to log in to the web server.

Brute-force is not the correct answer, because it is a broader term that encompasses different types of attacks that involve trying different variations of symbols or words until the correct password is found. Password spraying is a specific type of brute force attack that uses a single common password against multiple accounts⁵. The logs show that the attacker is using password spraying, not brute force in general, to try to gain access to the web server. References = 1: Password spraying: An overview of password spraying attacks ... - Norton, 2: Security: Credential Stuffing vs. Password Spraying - Baeldung, 3: Brute Force Attack: A definition + 6 types to know | Norton, 4: What is a Pass-the-Hash Attack? - CrowdStrike, 5: What is a Brute Force Attack? | Definition, Types & How It Works - Fortinet

NEW QUESTION 14

Which of the following would be the best ways to ensure only authorized personnel can access a secure facility? (Select two).

- A. Fencing
- B. Video surveillance
- C. Badge access
- D. Access control vestibule
- E. Sign-in sheet
- F. Sensor

Answer: CD

Explanation:

Badge access and access control vestibule are two of the best ways to ensure only authorized personnel can access a secure facility. Badge access requires the personnel to present a valid and authenticated badge to a reader or scanner that grants or denies access based on predefined rules and permissions. Access control vestibule is a physical security measure that consists of a small room or chamber with two doors, one leading to the outside and one leading to the secure area. The personnel must enter the vestibule and wait for the first door to close and lock before the second door can be opened. This prevents tailgating or piggybacking by unauthorized individuals. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 4, pages 197-1981

NEW QUESTION 16

A newly identified network access vulnerability has been found in the OS of legacy IoT devices. Which of the following would best mitigate this vulnerability quickly?

- A. Insurance
- B. Patching
- C. Segmentation
- D. Replacement

Answer: C

Explanation:

Segmentation is a technique that divides a network into smaller subnetworks or segments, each with its own security policies and controls. Segmentation can help mitigate network access vulnerabilities in legacy IoT devices by isolating them from other devices and systems, reducing their attack surface and limiting the potential impact of a breach. Segmentation can also improve network performance and efficiency by reducing congestion and traffic. Patching, insurance, and replacement are other possible strategies to deal with network access vulnerabilities, but they may not be feasible or effective in the short term. Patching may not be available or compatible for legacy IoT devices, insurance may not cover the costs or damages of a cyberattack, and replacement may be expensive and time-consuming. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 142-143

NEW QUESTION 19

A systems administrator is working on a solution with the following requirements:

- Provide a secure zone.
- Enforce a company-wide access control policy.
- Reduce the scope of threats.

Which of the following is the systems administrator setting up?

- A. Zero Trust
- B. AAA
- C. Non-repudiation
- D. CIA

Answer: A

Explanation:

Zero Trust is a security model that assumes no trust for any entity inside or outside the network perimeter and requires continuous verification of identity and permissions. Zero Trust can provide a secure zone by isolating and protecting sensitive data and resources from unauthorized access. Zero Trust can also enforce a company-wide access control policy by applying the principle of least privilege and granular segmentation for users, devices, and applications. Zero Trust can reduce the scope of threats by preventing lateral movement and minimizing the attack surface.

References:

? 5: This source explains the concept and benefits of Zero Trust security and how it differs from traditional security models.

? 8: This source provides an overview of Zero Trust identity security and how it can help verify the identity and integrity of users and devices.

NEW QUESTION 20

Which of the following has been implemented when a host-based firewall on a legacy Linux system allows connections from only specific internal IP addresses?

- A. Compensating control
- B. Network segmentation

- C. Transfer of risk
- D. SNMP traps

Answer: A

Explanation:

A compensating control is a security measure that is implemented to mitigate the risk of a vulnerability or a weakness that cannot be resolved by the primary control. A compensating control does not prevent or eliminate the vulnerability or weakness, but it can reduce the likelihood or impact of an attack. A host-based firewall on a legacy Linux system that allows connections from only specific internal IP addresses is an example of a compensating control, as it can limit the exposure of the system to potential threats from external or unauthorized sources. A host-based firewall is a software application that monitors and filters the incoming and outgoing network traffic on a single host, based on a set of rules or policies. A legacy Linux system is an older version of the Linux operating system that may not be compatible with the latest security updates or patches, and may have known vulnerabilities or weaknesses that could be exploited by attackers. References = Security Controls – SY0-601 CompTIA Security+ : 5.1, Security Controls – CompTIA Security+ SY0-501 – 5.7, CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 5, page 240. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 5.1, page 18.

NEW QUESTION 22

A company requires hard drives to be securely wiped before sending decommissioned systems to recycling. Which of the following best describes this policy?

- A. Enumeration
- B. Sanitization
- C. Destruction
- D. Inventory

Answer: B

Explanation:

Sanitization is the process of removing sensitive data from a storage device or a system before it is disposed of or reused. Sanitization can be done by using software tools or hardware devices that overwrite the data with random patterns or zeros, making it unrecoverable. Sanitization is different from destruction, which is the physical damage of the storage device to render it unusable. Sanitization is also different from enumeration, which is the identification of network resources or devices, and inventory, which is the tracking of assets and their locations. The policy of securely wiping hard drives before sending decommissioned systems to recycling is an example of sanitization, as it ensures that no confidential data can be retrieved from the recycled devices. References = Secure Data Destruction – SY0-601 CompTIA Security+ : 2.7, video at 1:00; CompTIA Security+ SY0-701 Certification Study Guide, page 387.

NEW QUESTION 23

A security analyst scans a company's public network and discovers a host is running a remote desktop that can be used to access the production network. Which of the following changes should the security analyst recommend?

- A. Changing the remote desktop port to a non-standard number
- B. Setting up a VPN and placing the jump server inside the firewall
- C. Using a proxy for web connections from the remote desktop server
- D. Connecting the remote server to the domain and increasing the password length

Answer: B

Explanation:

A VPN is a virtual private network that creates a secure tunnel between two or more devices over a public network. A VPN can encrypt and authenticate the data, as well as hide the IP addresses and locations of the devices. A jump server is a server that acts as an intermediary between a user and a target server, such as a production server. A jump server can provide an additional layer of security and access control, as well as logging and auditing capabilities. A firewall is a device or software that filters and blocks unwanted network traffic based on predefined rules. A firewall can protect the internal network from external threats and limit the exposure of sensitive services and ports. A security analyst should recommend setting up a VPN and placing the jump server inside the firewall to improve the security of the remote desktop access to the production network. This way, the remote desktop service will not be exposed to the public network, and only authorized users with VPN credentials can access the jump server and then the production server. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 8: Secure Protocols and Services, page 382-383 1; Chapter 9: Network Security, page 441-442 1

NEW QUESTION 28

Which of the following scenarios describes a possible business email compromise attack?

- A. An employee receives a gift card request in an email that has an executive's name in the display field of the email.
- B. Employees who open an email attachment receive messages demanding payment in order to access files.
- C. A service desk employee receives an email from the HR director asking for log-in credentials to a cloud administrator account.
- D. An employee receives an email with a link to a phishing site that is designed to look like the company's email portal.

Answer: A

Explanation:

A business email compromise (BEC) attack is a type of phishing attack that targets employees who have access to company funds or sensitive information. The attacker impersonates a trusted person, such as an executive, a vendor, or a client, and requests a fraudulent payment, a wire transfer, or confidential data. The attacker often uses social engineering techniques, such as urgency, pressure, or familiarity, to convince the victim to comply with the request¹².

In this scenario, option A describes a possible BEC attack, where an employee receives a gift card request in an email that has an executive's name in the display field of the email. The email may look like it is coming from the executive, but the actual email address may be spoofed or compromised. The attacker may claim that the gift cards are needed for a business purpose, such as rewarding employees or clients, and ask the employee to purchase them and send the codes. This is a common tactic used by BEC attackers to steal money from unsuspecting victims³⁴.

Option B describes a possible ransomware attack, where malicious software encrypts the files on a device and demands a ransom for the decryption key. Option C describes a possible credential harvesting attack, where an attacker tries to obtain the login information of a privileged account by posing as a legitimate authority. Option D describes a possible phishing attack, where an attacker tries to lure the victim to a fake website that mimics the company's email portal and capture their credentials. These are all types of cyberattacks, but they are not examples of BEC attacks. References = 1: Business Email Compromise - CompTIA Security+ SY0-701 - 2.2 2: CompTIA Security+ SY0-701 Certification Study Guide 3: Business Email Compromise: The 12 Billion Dollar Scam 4: TOTAL: CompTIA Security+ Cert (SY0-701) | Udemy

NEW QUESTION 32

A client demands at least 99.99% uptime from a service provider's hosted security services. Which of the following documents includes the information the service provider should return to the client?

- A. MOA
- B. SOW
- C. MOU
- D. SLA

Answer: D

Explanation:

A service level agreement (SLA) is a document that defines the level of service expected by a customer from a service provider, indicating the metrics by which that service is measured, and the remedies or penalties, if any, should the agreed-upon levels not be achieved. An SLA can specify the minimum uptime or availability of a service, such as 99.99%, and the consequences for failing to meet that standard. A memorandum of agreement (MOA), a statement of work (SOW), and a memorandum of understanding (MOU) are other types of documents that can be used to establish a relationship between parties, but they do not typically include the details of service levels and performance metrics that an SLA does. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 16-17

NEW QUESTION 37

While troubleshooting a firewall configuration, a technician determines that a "deny any" policy should be added to the bottom of the ACL. The technician updates the policy, but the new policy causes several company servers to become unreachable. Which of the following actions would prevent this issue?

- A. Documenting the new policy in a change request and submitting the request to change management
- B. Testing the policy in a non-production environment before enabling the policy in the production network
- C. Disabling any intrusion prevention signatures on the 'deny any' policy prior to enabling the new policy
- D. Including an 'allow any' policy above the 'deny any' policy

Answer: B

Explanation:

A firewall policy is a set of rules that defines what traffic is allowed or denied on a network. A firewall policy should be carefully designed and tested before being implemented, as a misconfigured policy can cause network disruptions or security breaches. A common best practice is to test the policy in a non-production environment, such as a lab or a simulation, before enabling the policy in the production network. This way, the technician can verify the functionality and performance of the policy, and identify and resolve any issues or conflicts, without affecting the live network. Testing the policy in a non-production environment would prevent the issue of the 'deny any' policy causing several company servers to become unreachable, as the technician would be able to detect and correct the problem before applying the policy to the production network. Documenting the new policy in a change request and submitting the request to change management is a good practice, but it would not prevent the issue by itself. Change management is a process that ensures that any changes to the network are authorized, documented, and communicated, but it does not guarantee that the changes are error-free or functional. The technician still needs to test the policy before implementing it.

Disabling any intrusion prevention signatures on the 'deny any' policy prior to enabling the new policy would not prevent the issue, and it could reduce the security of the network. Intrusion prevention signatures are patterns that identify malicious or unwanted traffic, and allow the firewall to block or alert on such traffic. Disabling these signatures would make the firewall less effective in detecting and preventing attacks, and it would not affect the reachability of the company servers.

Including an 'allow any' policy above the 'deny any' policy would not prevent the issue, and it would render the 'deny any' policy useless. A firewall policy is processed from top to bottom, and the first matching rule is applied. An 'allow any' policy would match any traffic and allow it to pass through the firewall, regardless of the source, destination, or protocol. This would negate the purpose of the 'deny any' policy, which is to block any traffic that does not match any of the previous rules. Moreover, an 'allow any' policy would create a security risk, as it would allow any unauthorized or malicious traffic to enter or exit the network. References = CompTIA Security+ SY0-701 Certification Study Guide, page 204- 205; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 2.1 - Network Security Devices, 8:00 - 10:00.

NEW QUESTION 38

Which of the following is a hardware-specific vulnerability?

- A. Firmware version
- B. Buffer overflow
- C. SQL injection
- D. Cross-site scripting

Answer: A

Explanation:

Firmware is a type of software that is embedded in a hardware device, such as a router, a printer, or a BIOS chip. Firmware controls the basic functions and operations of the device, and it can be updated or modified by the manufacturer or the user. Firmware version is a hardware-specific vulnerability, as it can expose the device to security risks if it is outdated, corrupted, or tampered with. An attacker can exploit firmware vulnerabilities to gain unauthorized access, modify device settings, install malware, or cause damage to the device or the network. Therefore, it is important to keep firmware updated and verify its integrity and authenticity. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 2, page 67. CompTIA Security+ SY0-701 Exam Objectives, Domain 2.1, page 10.

NEW QUESTION 39

A company is planning to set up a SIEM system and assign an analyst to review the logs on a weekly basis. Which of the following types of controls is the company setting up?

- A. Corrective
- B. Preventive
- C. Detective
- D. Deterrent

Answer: C

Explanation:

A detective control is a type of control that monitors and analyzes the events and activities in a system or a network, and alerts or reports when an incident or a violation occurs. A SIEM (Security Information and Event Management) system is a tool that collects, correlates, and analyzes the logs from various sources, such as firewalls, routers, servers, or applications, and provides a centralized view of the security status and incidents. An analyst who reviews the logs on a weekly basis can identify and investigate any anomalies, trends, or patterns that indicate a potential threat or a breach. A detective control can help the company to respond quickly and effectively to the incidents, and to improve its security posture and resilience. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 1, page 23. CompTIA Security+ SY0-701 Exam Objectives, Domain 4.3, page 14.

NEW QUESTION 42

Which of the following automation use cases would best enhance the security posture of an organization by rapidly updating permissions when employees leave a company?

- A. Provisioning resources
- B. Disabling access
- C. Reviewing change approvals
- D. Escalating permission requests

Answer: B

Explanation:

Disabling access is an automation use case that would best enhance the security posture of an organization by rapidly updating permissions when employees leave a company. Disabling access is the process of revoking or suspending the access rights of a user account, such as login credentials, email, VPN, cloud services, etc. Disabling access can prevent unauthorized or malicious use of the account by former employees or attackers who may have compromised the account. Disabling access can also reduce the attack surface and the risk of data breaches or leaks. Disabling access can be automated by using scripts, tools, or workflows that can trigger the action based on predefined events, such as employee termination, resignation, or transfer. Automation can ensure that the access is disabled in a timely, consistent, and efficient manner, without relying on manual intervention or human error.

References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, Chapter 5: Identity and Access Management, page 2131. CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 5: Identity and Access Management, page 2132.

NEW QUESTION 45

An organization's internet-facing website was compromised when an attacker exploited a buffer overflow. Which of the following should the organization deploy to best protect against similar attacks in the future?

- A. NGFW
- B. WAF
- C. TLS
- D. SD-WAN

Answer: B

Explanation:

A buffer overflow is a type of software vulnerability that occurs when an application writes more data to a memory buffer than it can hold, causing the excess data to overwrite adjacent memory locations. This can lead to unexpected behavior, such as crashes, errors, or code execution. A buffer overflow can be exploited by an attacker to inject malicious code or commands into the application, which can compromise the security and functionality of the system. An organization's internet-facing website was compromised when an attacker exploited a buffer overflow. To best protect against similar attacks in the future, the organization should deploy a web application firewall (WAF). A WAF is a type of firewall that monitors and filters the traffic between a web application and the internet. A WAF can detect and block common web attacks, such as buffer overflows, SQL injections, cross-site scripting (XSS), and more. A WAF can also enforce security policies and rules, such as input validation, output encoding, and encryption. A WAF can provide a layer of protection for the web application, preventing attackers from exploiting its vulnerabilities and compromising its data. References = Buffer Overflows – CompTIA Security+ SY0-701 – 2.3, Web Application Firewalls – CompTIA Security+ SY0-701 – 2.4, [CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition]

NEW QUESTION 49

A security team is reviewing the findings in a report that was delivered after a third party performed a penetration test. One of the findings indicated that a web application form field is vulnerable to cross-site scripting. Which of the following application security techniques should the security analyst recommend the developer implement to prevent this vulnerability?

- A. Secure cookies
- B. Version control
- C. Input validation
- D. Code signing

Answer: C

Explanation:

Input validation is a technique that checks the user input for any malicious or unexpected data before processing it by the web application. Input validation can prevent cross-site scripting (XSS) attacks, which exploit the vulnerability of a web application to execute malicious scripts in the browser of a victim. XSS attacks can compromise the confidentiality, integrity, and availability of the web application and its users. Input validation can be implemented on both the client-side and the server-side, but server-side validation is more reliable and secure. Input validation can use various methods, such as whitelisting, blacklisting, filtering, escaping, encoding, and sanitizing the input data. References = CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 2, page 70. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 3.2, page 11. Application Security – SY0-601 CompTIA Security+ : 3.2

NEW QUESTION 52

A systems administrator wants to prevent users from being able to access data based on their responsibilities. The administrator also wants to apply the required access structure via a simplified format. Which of the following should the administrator apply to the site recovery resource group?

- A. RBAC
- B. ACL
- C. SAML
- D. GPO

Answer: A

Explanation:

RBAC stands for Role-Based Access Control, which is a method of restricting access to data and resources based on the roles or responsibilities of users. RBAC simplifies the management of permissions by assigning roles to users and granting access rights to roles, rather than to individual users. RBAC can help enforce the principle of least privilege and reduce the risk of unauthorized access or data leakage. The other options are not as suitable for the scenario as RBAC, as they either do not prevent access based on responsibilities, or do not apply a simplified format. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 133 1

NEW QUESTION 53

Which of the following roles, according to the shared responsibility model, is responsible for securing the company's database in an IaaS model for a cloud environment?

- A. Client
- B. Third-party vendor
- C. Cloud provider
- D. DBA

Answer: A

Explanation:

According to the shared responsibility model, the client and the cloud provider have different roles and responsibilities for securing the cloud environment, depending on the service model. In an IaaS (Infrastructure as a Service) model, the cloud provider is responsible for securing the physical infrastructure, such as the servers, storage, and network devices, while the client is responsible for securing the operating systems, applications, and data that run on the cloud infrastructure. Therefore, the client is responsible for securing the company's database in an IaaS model for a cloud environment, as the database is an application that stores data. The client can use various security controls, such as encryption, access control, backup, and auditing, to protect the database from unauthorized access, modification, or loss. The third-party vendor and the DBA (Database Administrator) are not roles defined by the shared responsibility model, but they may be involved in the implementation or management of the database security. References = CompTIA Security+ SY0-701 Certification Study Guide, page 263- 264; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 3.1 - Cloud and Virtualization, 5:00 - 7:40.

NEW QUESTION 57

Which of the following describes the reason root cause analysis should be conducted as part of incident response?

- A. To gather IoCs for the investigation
- B. To discover which systems have been affected
- C. To eradicate any trace of malware on the network
- D. To prevent future incidents of the same nature

Answer: D

Explanation:

Root cause analysis is a process of identifying and resolving the underlying factors that led to an incident. By conducting root cause analysis as part of incident response, security professionals can learn from the incident and implement corrective actions to prevent future incidents of the same nature. For example, if the root cause of a data breach was a weak password policy, the security team can enforce a stronger password policy and educate users on the importance of password security. Root cause analysis can also help to improve security processes, policies, and procedures, and to enhance security awareness and culture within the organization. Root cause analysis is not meant to gather IoCs (indicators of compromise) for the investigation, as this is a task performed during the identification and analysis phases of incident response. Root cause analysis is also not meant to discover which systems have been affected or to eradicate any trace of malware on the network, as these are tasks performed during the containment and eradication phases of incident response. References = CompTIA Security+ SY0-701 Certification Study Guide, page 424-425; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 5.1 - Incident Response, 9:55 - 11:18.

NEW QUESTION 60

Which of the following threat actors is the most likely to use large financial resources to attack critical systems located in other countries?

- A. Insider
- B. Unskilled attacker
- C. Nation-state
- D. Hacktivist

Answer: C

Explanation:

A nation-state is a threat actor that is sponsored by a government or a political entity to conduct cyberattacks against other countries or organizations. Nation-states have large financial resources, advanced technical skills, and strategic objectives that may target critical systems such as military, energy, or infrastructure. Nation-states are often motivated by espionage, sabotage, or warfare. References = 1: CompTIA Security+ SY0-701 Certification Study Guide, page 542: Threat Actors – CompTIA Security+ SY0-701 – 2.1, video by Professor Messer.

NEW QUESTION 61

Which of the following security control types does an acceptable use policy best represent?

- A. Detective
- B. Compensating
- C. Corrective

D. Preventive

Answer: D

Explanation:

An acceptable use policy (AUP) is a set of rules that govern how users can access and use a corporate network or the internet. The AUP helps companies minimize their exposure to cyber security threats and limit other risks. The AUP also serves as a notice to users about what they are not allowed to do and protects the company against misuse of their network. Users usually have to acknowledge that they understand and agree to the rules before accessing the network¹. An AUP best represents a preventive security control type, because it aims to deter or stop potential security incidents from occurring in the first place. A preventive control is proactive and anticipates possible threats and vulnerabilities, and implements measures to prevent them from exploiting or harming the system or the data. A preventive control can be physical, technical, or administrative in nature².

Some examples of preventive controls are:

- ? Locks, fences, or guards that prevent unauthorized physical access to a facility or a device
- ? Firewalls, antivirus software, or encryption that prevent unauthorized logical access to a network or a system
- ? Policies, procedures, or training that prevent unauthorized or inappropriate actions or behaviors by users or employees

An AUP is an example of an administrative preventive control, because it defines the policies and procedures that users must follow to ensure the security and proper use of the network and the IT resources. An AUP can prevent users from engaging in activities that could compromise the security, performance, or availability of the network or the system, such as:

- ? Downloading or installing unauthorized or malicious software
- ? Accessing or sharing sensitive or confidential information without authorization or encryption
- ? Using the network or the system for personal, illegal, or unethical purposes
- ? Bypassing or disabling security controls or mechanisms
- ? Connecting unsecured or unapproved devices to the network

By enforcing an AUP, a company can prevent or reduce the likelihood of security breaches, data loss, legal liability, or reputational damage caused by user actions or inactions³.

References = 1: How to Create an Acceptable Use Policy - CoreTech, 2: [Security Control Types: Preventive, Detective, Corrective, and Compensating], 3: Why You Need A

Corporate Acceptable Use Policy - CompTIA

NEW QUESTION 64

An analyst is evaluating the implementation of Zero Trust principles within the data plane. Which of the following would be most relevant for the analyst to evaluate?

- A. Secured zones
- B. Subject role
- C. Adaptive identity
- D. Threat scope reduction

Answer: A

Explanation:

Secured zones are a key component of the Zero Trust data plane, which is the layer where data is stored, processed, and transmitted. Secured zones are logical or physical segments of the network that isolate data and resources based on their sensitivity and risk. Secured zones enforce granular policies and controls to prevent unauthorized access and lateral movement within the network¹.

References: CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 5, page 255.

NEW QUESTION 68

A systems administrator set up a perimeter firewall but continues to notice suspicious connections between internal endpoints. Which of the following should be set up in order to mitigate the threat posed by the suspicious activity?

- A. Host-based firewall
- B. Web application firewall
- C. Access control list
- D. Application allow list

Answer: A

Explanation:

A host-based firewall is a software application that runs on an individual endpoint and filters the incoming and outgoing network traffic based on a set of rules. A host-based firewall can help to mitigate the threat posed by suspicious connections between internal endpoints by blocking or allowing the traffic based on the source, destination, port, protocol, or application. A host-based firewall is different from a web application firewall, which is a type of firewall that protects web applications from common web-based attacks, such as SQL injection, cross-site scripting, and session hijacking. A host-based firewall is also different from an access control list, which is a list of rules that control the access to network resources, such as files, folders, printers, or routers. A host-based firewall is also different from an application allow list, which is a list of applications that are authorized to run on an endpoint, preventing unauthorized or malicious applications from executing. References: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 254

NEW QUESTION 70

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

SY0-701 Practice Exam Features:

- * SY0-701 Questions and Answers Updated Frequently
- * SY0-701 Practice Questions Verified by Expert Senior Certified Staff
- * SY0-701 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * SY0-701 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The SY0-701 Practice Test Here](#)